

ISSUE: 1002300 / 0809

**HIGHLY EFFECTIVE WATER
REPELLENT PROTECTION****DEEP PENETRATING
OIL-BASED TREATMENT****LIGHT & DARK SHADES
SAFE TO USE****Description:**

LANGLOW CREO-COAT is a unique oil-based wood treatment which demonstrates deep penetrating, water-repellent properties, enhancing the timber grain structure whilst providing long-term protection against the damage caused by moisture ingress, which can degrade and rot the structure and appearance of timber facings. It replaces the natural wood oils lost through weathering and is recommended for use on exterior, rough sawn garden timbers and should not be used on internal structures. LANGLOW CREO-COAT is available as either a DARK or LIGHT coloured solution and retains many of the properties associated with traditional Creosote when it comes to improving the definition of the natural timber knots and grain structure whilst still retaining the characteristic odour familiar to all Creosote users.

Preparation:

Ensure all Garden timbers are structurally sound, dry and free from surface growths of moss, lichen and algae. Care should be taken to protect all valuable plants and foliage from contact with the product during application. Children and pets should also be kept away from treated timbers until they are completely dry. Timbers previously treated with traditional Creosote or a solvent based wood preservative will readily accept being re-treated with LANGLOW CREO-COAT, however sealed or painted timbers should be stripped back to bare wood before coating with this product.

Application:

LANGLOW CREO-COAT can be applied by brush, spray or dip methods using consecutive coats to achieve a deeper colour shade where necessary. Use a broad-bristled brush and apply evenly, soaking the timbers to refusal to achieve best results. Spray applications should be made with a coarse droplet spray nozzle held within 300mm of the treated timber at all times to limit wastage and reduce the risk of contaminating surrounding plants and structures. Always pay extra attention to ensuring exposed end-grain timbers are fully saturated. For timbers being set in the ground it is recommended to over-coat the submerged section with Bitumen Paint to protect against groundwater saturation.

Coverage:

Depending upon the texture and porosity of the timber to be treated, LANGLOW CREO-COAT when applied as single coat will cover at the rate of 1 litre per 6 to 8 square metres, either by brush or spray application method.

HEALTH & SAFETY:**HARMFUL; DANGEROUS FOR THE ENVIRONMENT****Harmful: may cause lung damage if swallowed****Irritating to eyes, respiratory system and skin****Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment****Limited evidence of a carcinogenic effect**

Keep out of the reach of children; Wear suitable protective clothing, gloves and eye/face protection

Avoid release to the environment. Refer to special instructions/safety data sheet

If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label

**HARMFUL****DANGEROUS FOR
THE ENVIRONMENT****Storage & Packaging:**

LANGLOW CREO-COAT is available in 4 litre & 20 litre poly bottles and 205 litre & 5 US gallon Export drums.

Store in cool, well-ventilated conditions away from direct sources of heat or ignition.

LANGLOW CREO-COAT is not flammable but is classified as UN3082 under the controls applied to the carriage of Dangerous goods

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.