

ISSUE: 47-2 / 0809

**EXCELLENT
INITIAL GRAB****FIXES ALL TYPES
OF WALL-COVERING****DRIES TO A CLEAR
SECURE BOND****Description:**

PALACE READY MIXED WALL-COVERING ADHESIVE is ready mixed for immediate use and is suitable for hanging vinyl wall-coverings including heavy-duty paper or fabric backed types, hessians, expanded polystyrene veneer and blow vinyl to all suitably prepared wall surfaces. This product contains a fungicidal preservative.

Surface Preparation:

Surfaces to be covered should be clean, dry & dust free. Highly absorbent walls should be primed with a dilution of 1 part adhesive to 1 part water to stabilise the surface. The priming coat must be allowed to dry before commencing hanging. Do not use this product at temperatures below 10°C.

Application:

Apply the adhesive liberally by brush or roller onto paper-backed wall-coverings and hang in the normal way to ensure the pattern continuity is maintained from strip to strip. For other types of wall-covering such as polystyrene veneers and Novamura, spread the adhesive directly to the wall and then hang the wall-covering. If any adhesive gets on the decorative surface of the wall-covering, remove immediately with a damp cloth. For paper backed HESSIAN the adhesive should be applied to the paper backing however on bare hessians always apply the adhesive to the wall. Clean tools immediately in water after use.

Coverage:

Approximately 5.5 sq. metres per kg

Storage & Packaging:

READY MIXED WALL-COVERING ADHESIVE is supplied in 1 litre; 2.5 litre & 5 litre tubs and has a storage life of not less than 12 months if kept in dry, un-opened conditions away from frost or elevated temperatures (> 35°C). Consult the READY MIXED WALL-COVERING ADHESIVE material safety data sheet for advice on handling and safety procedures. Should further more specific technical information be required, contact the Palace Technical helpline on 0151 486 6101.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.