

Ref: 067BPD-TWP077– Wood Preserver:

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY:

| 1.1 Product Name: | LANGLOW WOOD PRESERVER – [TWP077] |
|-----------------------------|---|
| 1.2 Applications: | Solvent based treatment for the prevention of dry rot & fungal degradation. |
| 1.3 Supplier: | Palace Chemicals Ltd; Speke Hall Industrial Estate; Speke; Liverpool; L24 1YA Tel: 0151 486 6101; Fax 0151 448 1982 e-mail: sales@palacechemicals.co.uk; web: www.palacechemicals.co.uk |
| 1.4 Emergency Telephone No. | Tel: 0151 486 6101 – Mon-Fri: 0800 - 1800 |

MATERIAL SAFETY DATA SHEET LANGLOW

2. HAZARDS IDENTIFICATION:

| 2.1 Classification : (EC 1272/2008) | H304 - Health EUH066; Asp. Tox. 1 |
|--|--|
| (| H412 - Environmental Aquatic Chronic 2 |
| 2.2 | |
| Label elements: | |
| Key Word: | DANGER |
| Hazard statements: | H227 – Combustible liquid |
| | H304 - May be fatal if swallowed and enters airways. H412 - Harmful to aquatic life with long lasting effects. |
| Precautionary | 11412 - Hammur to aquatic me with long lasting enects. |
| statements: | P101 - If medical advice is needed, have product container or label at hand. |
| | P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| | P102 - Keep out of reach of children. |
| | P103 - Read label before use. |
| | P301 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting. |
| | P260 - Do not breathe vapours. |
| | P262 - Do not get in eyes, on skin, or on clothing. |
| 2.3 Other hazards: | P233 Keep container tightly closed. P273 Avoid release to the environment. |
| | P403/235 Store in a well-ventilated place. Keep cool. |
| | P501 – Dispose of containers & container in accordance with local authority regulations for hazardous |
| | liquid & biocides |
| Supplemental information: | Contains 3-lodo-2-propynyl butylcarbamate and propiconazole (ISO). May produce an allergic reaction. |
| | READ ALL PRECAUTIONS BEFORE USE - FOR PROFESSIONAL & CONSUMER USERS Containers will be fitted with child resistant closures and Tactile Danger Warnings |

3. COMPOSITION / INFORMATION ON INGREDIENTS:

| 3.2 Mixtures: WOOD PRE | | | WOOD PRESERVE | R PREPARATION | |
|---|------------|------------|----------------|---|--|
| Name: | CAS No.: | EC Number: | Concentration: | Classification: | |
| Naphtha (petroleum) hydro-treated heavy | 64742-48-9 | 265-150-3 | 84.0% | Acute Tox 1 H304; | |
| Propiconazole | 60207-90-1 | 262-104-4 | 0.24% | Acute Tox 4 H302; Skin Sens 1 H317; Aquatic acute H400; Aquatic chronic H410 | |
| 3-lodo-Propynyl Butyl Carbamate | 55406-53-6 | 259-627-5 | 0.75% | Acute Tox 4 H302; Skin Sens 1 H317; Eye Dam 1 H318; Acute Tox 3 H331; STOT RE 1 H372; Aquatic acute H400; Aquatic chronic H410 | |
| Tri-Propyleneglycol Methyl ether | 25498-49-1 | 247-045-4 | 1.5% | Not classified | |
| Long oil alkyd resin | 68527-28-6 | | 2.0% | Not classified | |
| Aromatic hydrocarbon binder | 71302-83-5 | | 4.0% | Not classified | |
| Di-Propylene glycol methyl ether | 34590-94-8 | 252-104-2 | 5.0% | Not classified | |



| 4.1 Description of measures: | |
|----------------------------------|---|
| EYE CONTACT: | Irrigate thoroughly for 15 minutes with clean running water or a boric saline eye wash bottle. Seek medical attention should eye irritation persist or become inflamed. |
| INHALATION: | Avoid working in a poorly ventilated, confined space. Remove to fresh air and rest. If irritation or breathing difficulties persist, seek medical attention. |
| SKIN CONTACT: | Wash off skin with warm soapy water. Remove contaminated clothing and launder regularly. Prolonged and unattended contact should be avoided. Where irritation to skin is apparent seek medical attention. |
| INGESTION: | Clean out mouth with copious volumes of water and drink plenty. Do not induce vomiting. Beware of aspiration if vomiting occurs. Seek prompt medical attention and show this data sheet |
| 4.2 Acute & Chronic symptoms: | |
| Inhalation: | Vapours inhaled in strong concentration have a narcotic effect on the central nervous system. Irritation of the respiratory tract due to excessive fumes causes headache, drowsiness or other effects to the central nervous system, loss of consciousness. |
| Ingestion: | Nausea, vomiting, abdominal pain. |
| Skin contact: | Prolonged or repeated contact may cause irritation and dry skin. |
| Eye Contact: | Burning feeling and temporary redness. |
| 4.3 Immediate medical attention: | This will be needed to resolve the most severe risk which is through ingestion as the product may enter the lungs due to its low viscosity and lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours). |

MATERIAL SAFETY DATA SHEET

LANGLOW

5. FIRE FIGHTING MEASURES:

| 5.1 Extinguishing media: | Dry powder; Foam, C02 – Do not use water jets. |
|-------------------------------|--|
| 5.2 Combustion Hazards: | Hazardous decomposition when subject to combustion – will produce noxious, irritating fumes. |
| 5.3 Advice for fire-fighters: | Use approved self-contained breathing apparatus. Only use a fine water spray to cool down heat affected containers – not burning product. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control. |


6. ACCIDENTAL RELEASE MEASURES:

| 6.1 Personal protection: | Ventilate area and eliminate all sources of ignition. Wear personal protective equipment recommended in section 8. |
|-----------------------------------|---|
| 6.2 Environmental precautions: | Do not allow spill to enter drains or watercourses. Form a dam with sand, earth or a boom. Absorb bund and scrape spillages onto sand, sawdust or absorbent granules. |
| 6.3 Spill removal methods: | Confine residues in clearly marked sealed containers for disposal in accordance with Local Authority regulations for flammable products – subject to special waste management controls. |
| 6.4 References to other sections: | Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. For waste disposal, see section 13. |

7. HANDLING & STORAGE:

| 7.1 Safe handling precautions: | Eliminate all sources of ignition. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Wear full protective clothing for prolonged exposure and/or high concentrations. Contaminated clothing and shoes must be discarded. Contaminated rags and cloths must be put in fireproof containers for disposal. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. |
|----------------------------------|--|
| 7.2 (a) Safe storage conditions: | Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Take precautionary measures against static discharges. |
| 7.2 (b) Incompatible materials: | Keep away from oxidisers, heat and flames. May attack some plastics, rubber and coatings. |
| 7.3 Specific end uses: | The identified uses for this product are detailed in Section 1.2. |





8.1 Control parameters

Substance:

Naphtha (petroleum) hydro-treated heavy 2-methoxymethyl ethoxy propanol

8 hour exposure limit WEL- 350 mg/M3 WEL- 308 mg/M3 **15 minute exposure limit** STEL- 600mg/M3 Source. Type

LANGLOV

DNEL's - (Derived No effect levels) for workers:

| DILLE 5 - (Dellived no elleot levelo) | | | | |
|---|---|------------------------|---|------------------|
| Exposure pattern: | Route | DNEL | Dose descriptor | |
| Long term systemic effects - | Dermal | 65 per 8 hours mg/m3 | Industry | |
| Long term systemic effects - | Inhalation | 310mg/M3 | | |
| Long term local effects - | Dermal | 15 mg/kg/day | Consumer | |
| Long term local effects - | Inhalation | 37.2mg/M3 | | |
| PNEC's - Predicted No effect conce | | nment): | | |
| Compartment: | PNEC | | Dose Descriptor | |
| Fresh water - | | | | |
| Sewage treatment - | | | | |
| 8.2 Exposure controls: Engineering controls: | | te general and local e | | ataction must be |
| Respiratory protections: | No specific recommendation is made, but appropriately specified respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. | | | |
| Hand protection: | Protective gloves must be used. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Use protective gloves made of nitrile. | | | |
| Eye protection: | BS 2092 approved safety Goggles should be worn for all applications to help prevent accidental face/eye contact. | | | |
| Other Protection: | Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. | | | |
| Hygiene measures: | Wash at the end toilet. Promptly | remove any clothing th | d before eating, smoking and using the nat becomes contaminated. Wash comes contaminated. Use appropriate | |

9. PHYSICAL & CHEMICAL PROPERTIES:

| Appearance: Odour: | Clear or coloured liquids Aromatic hydrocarbon | Relative density: Water solubility: | 0.795 – 0.815 Nil |
|--------------------------|---|--|----------------------|
| Odour threshold: | Lower | Solubility in oils: | 100% |
| | | • | |
| pH: | 5.5 – 6.5 | Partition coefficient (Kow): | n/a |
| Flash point: | 63'C | Auto-ignition temperature: | 238'C |
| Melting point: | n/a | Decomposition temperature: | n/a |
| Boiling point: | n/a | Surface tension: | 0.0245 N/m @ 25 'C |
| Evaporation rate: | < 1 (butyl acetate = 1) | Viscosity: | 0.023 m2/s 40 |
| Upper/Lower Flam limits: | n/a | Explosive properties: | n/a |
| Vapour pressure: | < 5 kPa 20 | Oxidising properties: | n/a |
| Vapour density: | n/a | Particle size: | n/a |
| | | | |



MATERIAL SAFETY DATA S

LANGLOV



| 10.1 Conditions to avoid: | None specified | 10.4 Reactivity: | Stable |
|------------------------------|--------------------------|----------------------------------|---|
| 10.2 Incompatible Materials: | Acids & Oxidising agents | 10.5 Chemical reactivity: | Stable under the prescribed storage conditions. |
| 10.3 Decomposition hazards: | Fire creates toxic fumes | 10.6 Risk of hazardous reaction: | None under normal use. |

11. TOXICOLOGICAL INFORMATION:

11.1 Information on toxicological effects: This product has not been exhaustively tested. Judgements on the expected toxicity of this product have been made based upon consideration of its' major components.

| Routes of exposure: | Inhalation, skin contact and ingestion. | Skin Corrosivity / Irritation: | May cause de-fatting of the skin, |
|------------------------|--|---------------------------------|--|
| Eye damage/irritation: | Burning feeling and temporary redness. | Respiratory/skin sensitisation: | n/a |
| Reproductive toxicity: | n/a | Germ cell Mutagenicity: | n/a |
| Acute Toxicity: | Propiconazole: LD 50 = 1517 mg/kg (oral rat) LD 50 > 4.0g mg/kg (dermal rat) | Carcinogenicity: | No evidence of carcinogenic properties |
| Acute Toxicity: | 3-lodo-Propynyl Butyl Carbamate: LD 50 > 2000 mg/kg (dermal rabbit) LD 50 = 1470 mg/kg (oral rat) | Aspiration hazard: | ASPIRATION HAZARD Cat 1 (chemical pneumonitis, potentially fatal). |
| 12. ECOLOGICAL INF | ORMATION: | | |

| 12.1 Ecotoxicity: | Propiconazole:12.4 Mobility in soil:EC 50 = 0.76 mg/ltr (Daphnia)LC 50 = 4.3 mg/ltr (Fish) | | 75% degradable in 28 days |
|-----------------------------------|--|-----------------------------|--|
| | 3-lodo-Propynyl Butyl Carbamate: EC 50 = 0.05 mg/ltr (Daphnia) LC 50 = 0.067 mg/ltr (trout) | | |
| 12.2 Bio-accumulative potential: | Negligible due to high volatility | 12.5 PBT and vPvB result: | Not Classified as PBT/vPvB |
| 12.3 Persistence & degradability: | The substance is readily biodegradable. | 12.6 Other adverse effects: | Toxic to aquatic life with long lasting effects |

13. DISPOSAL CONSIDERATIONS:

13.1 Waste treatment Methods: Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Waste is suitable for incineration. Rags and the like, moistened with flammable liquids, must be discarded into designated fireproof bucket. Where possible packaging should be collected for reuse or recycling. Empty used containers should be disposed of as waste code 15 01 10 packaging containing residues of or contaminated by dangerous substances. When used the removed sludge should be disposed of using waste code 08 01 13 for paint & varnish sludge materials. Any absorbents used for clearing up soils should be disposed of using waste code 15 02 02, for absorbents contaminated by dangerous substances.



14. TRANSPORT INFORMATION:

Transport Labels:



| Regulatory Code (Land, Sea & Air): | ADR | IMDG | ICAO |
|------------------------------------|---|---|--|
| 14.1 UN No.: | 3082 | 3082 | 3082 |
| 14.2 Proper shipping name: | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. |
| 14.3 ADR Packing Group: | III | III | III |
| 14.4 Transport Hazard Class: | 9 | 9 | 9 |
| 14.5 Environmental hazards. | Marine Pollutant | Marine Pollutant | Marine Pollutant |
| 14.6 Hazard identification No.: | 90 | 90 | 90 |
| 14.7 Transport category (ADR): | 3 | 3 | 3 |

15. REGULATORY INFORMATION:

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture All components are listed as existing substances in Europe

UK Regulatory References:

This product has been assessed under the CHIP Regulations and Control of Pesticides Regulations 1986. Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Environmental Listing - Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980. Statutory Instruments:

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply. **Guidance Notes:**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108). EU Legislation:

Dangerous Substance Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation (EU) No 528/2012 of the European Parliament - The market and use of biocidal products.

This product is approved under the Biocidal Products Regulation [528/2012] - Authorisation No. UK-2016-1015 WOOD PRESERVATIVE - Type PT 8 For Non-Professional Preventative Use - Application Class 1, 2 & 3

National Regulations:

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.

Authorisations (Title VII Regulation 1907/2006) - No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006) - No specific restrictions of use are noted for this product. Chemical safety assessment

15.2

A chemical safety assessment has not been carried out for this product.



16. OTHER INFORMATION:

| Last revision date: SDS No.: List of abbreviations used in this CAS CLP DSD DPD PBT REACH vPvB | |
|---|--|
| References: Classification methods: H Phrases in section 3: | Volume VII Approved supply list; EH40; Croner; Bulk supplier data sheets H304 - May be fatal if swallowed and enters airways. H302 – Harmful if swallowed H317 – May cause an allergic skin reaction H318 – Causes serious eye damage H335 – May cause respiratory irritation H319 – Causes serious eye irritation H400 – Very Toxic to aquatic life H410 – Very toxic to aquatic life with long lasting effects. H412 – Harmful to aquatic life with long lasting effects. |
| Training for workers: Disclaimer: | The information supplied in this safety data sheet is intended to assist in the use of the above product without risk to safety and health and is based on current knowledge and experience of the associated physico-chemical hazards. The data does not signify any warranty with regard to the product's properties. This information may be used to assist in formulating a COSHH risk assessment if applied at work. This data sheet complies with EC Directive 91/155EC. |