



# TILE AFTERCARE MARBLE & STONE IMPREGNATOR



Issue 1 – ACMSI / 0815

**FOR USE ON SMOOTH  
MARBLE & STONE SURFACES**

**PROTECTS AGAINST WATER  
AND OIL BASED STAINS**

**ONE COAT APPLICATION  
DRIES TO A MATT FINISH**

## DESCRIPTION:

Marble & Natural Stone Impregnator is designed to penetrate into porous and semi-porous tiled surfaces and grout joints to form an oil or water repellent barrier which allows any damp still in the substrate to evaporate but restricts any further moisture ingress which can damage the structure and tarnish the surface finish. Ideal for use on smooth-finished porous and semi-porous marble, travertine and natural stone surfaces.

## APPLICATION:

Ensure the surface is thoroughly clean, dry and free of all surface deposits. An application of All Purpose Tile Cleaner the day before may assist in achieving an ideal clean surface. Floors must be left to dry for at least 3 days and any under-floor heating switched off 24 hours prior to applying the Impregnator solution. Apply the product neat with a smooth paint roller or non-fibrous sponge or cloth working in one direction and allowed to soak in for about 5 – 10 minutes before promptly wiping away any excess treatment with a dry cloth to ensure an even coat is achieved. Highly porous surfaces may require a repeat treatment 2 to 3 hours later. Drying time under ambient conditions will be about 3 to 4 hours. The final appearance should be a matt finish however where an excessive application has caused a sheen-finish to remain, but is not desired, wipe down with a cloth soaked in white spirit to remove excess treatment from the surface.

## COVERAGE:

Depending on surface texture and porosity, one litre of Impregnator will be sufficient to protect between 10 - 20 square metres of marble type smooth porous surface per 1 litre pack for a single coat application.

## PROPERTIES:

Palace Marble & Natural Stone Impregnator is a spirit based water & oil repellent treatment ideal for application onto marble, travertine, slate and natural stone where protection is required from stains caused by liquid absorption, but the appearance of the tile is to remain unaltered. This product is also ideal for protecting flagstone and paving from water ingress and can be used in both interior and exterior applications.

## HEALTH & SAFETY PRECAUTIONS:

**Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes damage to organs Central nervous system through prolonged or repeated exposure if inhaled. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do NOT induce vomiting. IF SWALLOWED: Immediately call a doctor / NHS Direct. IF ON SKIN: Wash with plenty of soap and water. Do not breathe vapours. IF INHALED: Remove victim to fresh air and keep in a position comfortable for breathing. Do not get in eyes, on skin, or on clothing. IF ON SKIN Remove immediately all contaminated clothing. Rinse skin with water/shower. Store in a well-ventilated place. Keep container tightly closed Keep cool.



The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

**PALACE CHEMICALS Ltd**

Speke Hall Industrial Estate; Speke; Liverpool; L24 1YA

Tel: 0151 486 6101 – Fax: 0151 448 1982

e-mail: sales@palacechemicals.co.uk

