

Ver 03 - PALCM 16.07.21

# CONTRACT-MATT

## HIGH OPACITY DECORATIVE EMULSION PAINT

- GIVES AMPLE TIME FOR NEW PLASTER TO DRY
- AVAILABLE IN WHITE AND MAGNOLIA
- HIGH OPACITY WITH A SOLID FIRST COAT FINISH
- CAN BE APPLIED OVER MOST TYPES OF INTERIOR SMOOTH & SEMI-POROUS SURFACES
- CAN BE APPLIED VIA BRUSH OR ROLLER



Brilliant White

Magnolia

### LANGLOW CONTRACT-MATT

Is a matt emulsion paint for interior use on wall and ceiling surfaces. Can be applied over most types of interior smooth and semi-porous surfaces.

MATT FINISH

HIGH OPACITY FIRST-COAT

# CONTRACT MATT

## High Opacity Decorative Emulsion Paint



### DESCRIPTION

**LANGLOW CONTRACT MATT** is a high opacity decorative water-borne matt emulsion for interior use on wall and ceiling surfaces, which can be applied over most types of interior smooth and semi-porous surface and is especially useful when painting over recently plastered walls and ceilings, where its micro-porous, breathable properties allow for full drying out of the newly constructed surface to be completed. **LANGLOW CONTRACT MATT** can be applied by brush or roller to give excellent hiding power and coverage over most surface types and dries out to a flat matt high opacity one-coat finish.

### SURFACE PREPARATION

Surfaces to be treated should be sound, clean, dry and free from loose flaking materials, oil and grease stains. Surface defects and cracks should be repaired with a suitable repair mix; filler or sealant. Scrape back to a firm edge all areas of existing loose flaking coatings and rub down thoroughly to 'key and feather' exposed edges of the original painted surface if applicable. Repair cracks or damaged areas with **LANGLOW POWDER FILLER** and allow it to dry before sanding to a smooth level and even finish.

### APPLICATION METHOD

Stir well before use, **LANGLOW CONTRACT MATT** can be applied either by a generously loaded brush or roller to achieve the best results. Two coats will normally be sufficient to give a satisfactory finish depending on the condition of the base substrate. Allow up to 6 hours between coats for drying under normal, well ventilated ambient conditions. Work down from the top of the elevation, keeping the sections painted small enough to ensure that the edges to be joined are still wet as work progresses.

### COVERAGE

5 litres of **LANGLOW CONTRACT MATT** will cover up to 25 square metres as a two-coat application over a smooth even surface, depending upon the condition, texture and porosity of the surface being coated. Care should be taken to ensure all windows and surfaces not intended for coverage are covered and well protected during the application of this product. Brushes and rollers can be readily cleaned immediately after use with warm soapy water. Splashes on skin should be cleaned off immediately with warm soapy water and not allowed to dry out unattended. Wear suitable protective clothing at all times during application, including boots, overalls, goggles and head protection.

### STORAGE AND PACKAGING

Store in a secure upright and sealed condition during transit and when in storage and protect from frost or temperatures less than 5°C or in excess of 35°C. Minimum shelf-life is 1 year from date of manufacture. **LANGLOW CONTRACT MATT** is available in re-sealable 10 litre buckets.

### HEALTH AND SAFETY

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Wear eye protection during paint application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of the reach of children. Do not use or store by hanging on a hook. **VOC Directive:** EU Limit value for this product (Cat A/c): 150 g/l (2007)/ 100g/l (2010). This product contains max 9 g/l VOC.

### QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

### TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at: <http://www.palacechemicals.co.uk>



EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

**PALACE CHEMICALS LTD**

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 – FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK