

Ver 03 - PALIW 11.08.21

INTRAPRUF

INTEGRAL WATERPROOFER FOR WALL RENDERS & SCREEDS

- CONCENTRATED WATERPROOFING ADMIXTURE
- INCREASED IMPERMEABILITY & REPELLENCY
- IMPROVES WORKABILITY & PROTECTS AGAINST MOISTURE INGRESS
- FOR WALL RENDERS & SCREEDS
- REDUCES WATER REQUIREMENT & IMPROVES STRENGTH



PALACE INTRAPRUF

Is a mortar/render water-proofing admixture, providing integral water-proofing activity. Designed to protect internal walls against moisture ingress from damp brickwork, which restricts penetrating dampness. Intrapruf enhances workability, in mortar, plaster, render and floor screeds.

RESTRICTS
DAMPNESS

RECOMMENDED FOR RE-PLASTERING
INTERNAL WALLS

INTRAPRUF

Integral Waterproofer For Wall Renders & Screeds



DESCRIPTION

PALACE INTRAPRUF WATERPROOFER is an aqueous solution of refined fatty acid based water repellents and sodium silicates for use as a mortar / render waterproofing admixture to give integral water-proofing activity, protecting internal walls against moisture ingress from capillary migration from damp brickwork and in external applications restricting penetrating dampness from rainwater. The water-reducing and plasticising properties of this additive also improves the density, strength and long-term durability for use in applications such as re-pointing; rendering; plastering and screeding.

PALACE INTRAPRUF WATERPROOFER imparts improved levels of workability, making for easier placement of mortar, plaster, render and floor screeds. The benefits of improved plasticising properties allows for levels of water reduction, which not only reduce the risk of drying shrinkage and cracking, but also results in higher long-term strength development in the hardened mortar. **PALACE INTRAPRUF WATERPROOFER** is the ideal additive for use when re-plastering internal walls following the installation of an injected damp-proof course. Its effectiveness in increasing the density and water-repellency of an internal render will inhibit the migration of salt-bearing moisture from brickwork above the DPC level, thus leaving the internal walls free to be finished and re-decorated without risk of further damage through dampness.

MIX GUIDELINES

To ensure that **PALACE INTRAPRUF WATERPROOFER** is adequately dispersed throughout the render / plaster mix, add to all the gauging liquid at a rate of 4.5 litres per 150 litres of water. This is approximately equivalent to about 320mls of **PALACE INTRAPRUF WATERPROOFER** per 25 kg of Portland cement. In general terms it is usually found that 500mls of **PALACE INTRAPRUF WATERPROOFER** when added to prepare a strong internal damp-proofing render of 1 part cement to 3 parts sand, will be sufficient to cover about 8 square metres at a depth typically of about 10mm.

Note: It is essential that water-proof renders are prepared using clean gauging liquid and washed dried, (salt-free - zone 3) sand, so that the full benefits of the products salt inhibiting properties can be demonstrated.

APPLICATION METHOD

Always add **PALACE INTRAPRUF WATERPROOFER** to the mixer water before charging with sand and cement. NEVER add direct to the dry cement or sand. To account for the water reducing properties of **PALACE INTRAPRUF WATERPROOFER** always start the mix with a minimal

required volume of water then top up to just about achieve the desired consistency, allowing complete & homogeneous mixing to be achieved at all stages, but avoid over mixing the mortar for a prolonged period as this may weaken the ultimate strength of the mix due to excessive aeration.

STORAGE AND PACKAGING

PALACE INTRAPRUF WATERPROOFER is supplied in 5 litre and 25 litre polythene containers and must be stored in sealed secure conditions away from sources of heat, or exposure to low temperatures and frost.

HEALTH AND SAFETY

IRRITATING in contact with skin and eyes in much the same way as the mixed cement mortars will irritate skin. Always wear suitable protective clothing, including overalls, alkali resistant gloves or gauntlets; safety boots and safety goggles where splashes are a perceived risk. Any clothing contaminated with splashes of **PALACE INTRAPRUF WATERPROOFER** should be changed and laundered immediately to prevent any risk of prolonged skin contact.



IRRITANT

A complete PALACE material safety data sheet is available on request or online at www.palacechemicals.co.uk

QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at: <http://www.palacechemicals.co.uk>

DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate, however it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.



EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

PALACE CHEMICALS LTD

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 - FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK