

Ver 03 - PALRMF 25.08.21

# READY MIXED FILLER

## FAST DRYING PLASTER BASED REPAIRING COMPOUND

- SUPER SMOOTH REPAIR COMPOUND
- NON-SHRINK
- BLENDS IN WITH FINISHING PLASTER
- SETS WITHIN 2 HOURS
- EASY TO MIX AND APPLY



### TECHNICAL SUMMARY

UNIT SIZES	600gm/1kg/Handy Tube
COLOUR	Brilliant White
DENSITY	18gm / cm <sup>3</sup>
SURFACE DRY TIME	1 - 2 hours
FULL CURE TIME	24 hours (@20°C)

### PALACE READY MIXED FILLER

Is a white acrylic, multi-purpose sealing and filling compound. Designed to repair gaps, cracks and depressions in and around interior structures. Suitable receiving surfaces include windows and door frames, decorative beams, skirting, plasterwork, render, architraves and other masonry based structures.

INTERIOR REPAIRS

CAN BE SANDED & OVERPAINTED ONCE DRY

# READY MIXED FILLER

## Fast Drying Plaster Based Repairing Compound



### DESCRIPTION

**LANGLOW READY MIXED FILLER** is a WHITE acrylic emulsion-based multi-purpose sealing & filling compound ideally suited for repairing gaps, cracks and depressions within and around interior structures such as window and door frames, decorative beams; skirting; plasterwork; render; architraves and other masonry based structures. Available in 600gm & 1 kg tubs for spatula applied gap repairs or as a 250ml hand extruded flexi-tube for sealing and filling fine cracks and joints in where shrinkage and slight movement is likely. This versatile filler can be applied into a prepared repair zone direct from the tub using a spatula or extruded from the flexi-tube with minimal hand pressure to form a tough durable surface repair which cures to a firm finish by the evaporation of moisture. **LANGLOW READY MIXED FILLER** is ideally for use in interior applications but can be sanded to a smooth finish and over-painted with oil or water-based paints where application in external environments is required.

### SURFACE PREPARATION

Ensure all repair areas voids and contact surfaces are dry, clean and free from dirt, grease and loose surface coatings. Try to ensure the edges of the repair zone are cut to a straight edges finish where possible and that all paint and surface coatings have been removed back to reveal bare substrate. Porous or friable substrates may need cutting to a firm edge to ensure the repair surface and the internal surface primed to ensure it is sound enough to achieve a secure permanent bond with the filler paste.

### APPLICATION METHOD

Apply the filler paste using a spatula to fill out all areas of the repair zone. In deep depressions, build up the repair in layers of not more than 10mm a time and allow each to dry before proceeding to the next application. When the repair zone is filled leave the paste slightly proud of the surrounding surface and when it is fully cured, use a smooth abrasive pad to sand back to the surrounding level. **LANGLOW READY MIXED FILLER** will form a skin after about 30 minutes and depending on the gap-layer depth, temperature and humidity will take up to 24 hours to achieve complete cure through the repair.

**LANGLOW READY MIXED FILLER is not suitable for use in un-covered exposed exterior locations or in fully immersed applications and the repair should not be painted over until it is fully cured and sanded smooth.**

### STORAGE AND PACKAGING

**LANGLOW READY MIXED FILLER** is supplied in 600gm & 1kg tubs (packed 12 per case) or as a "HANDY-PACK" flexi-tube where fine surface repairs are encountered. Both types have a storage life of not less than 12 months if kept in dry, un-opened conditions.

TECHNICAL SUMMARY	
UNIT SIZE	600gm/1kg/Handy Tube
COLOURS	Brilliant White
DENSITY	18gm / cm <sup>3</sup>
SURFACE DRY TIME	1 - 2 hours
FULL CURE TIME	24 hours (@20°C)

### HEALTH AND SAFETY

A complete PALACE material safety data sheet is available on request or online at [www.palacechemicals.co.uk](http://www.palacechemicals.co.uk)

### QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

### TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at:

<http://www.palacechemicals.co.uk>

### DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate, however it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.



EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

**PALACE CHEMICALS LTD**

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 – FAX: 0151 448 1982

E-MAIL: [SALES@PALACECHEMICALS.CO.UK](mailto:SALES@PALACECHEMICALS.CO.UK)