

Issue 1 – WP151 / 0510

**WATER REPELLENT  
TRADITIONAL SURFACE SEALER****PROTECTS & ENHANCES  
SMOOTH TIMBER SURFACES****FAST DRYING  
SOLVENT BASED****DESCRIPTION:**

LANGLOW WAX POLISH is a traditional water repellent protective treatment with natural waxes, pure turpentine oil and other solvents to protect and enhances the appearance of a range of surface types including smooth wooden flooring, furniture, doors, beams, frames and on other materials such as linoleum and natural stone. It leaves a high sheen surface finish which is water repellent and restricts any further moisture ingress and dirt accumulation which can damage the appearance and long-term durability of the surface finish.

**PREPARATION:**

On previously waxed surfaces it is recommended to strip the old wax-layers with LANGLOW OLD WOOD REVIVER before sanding the exposed timber surface using a disc or paper graded as appropriate to bring out the best features of the type of timber being treated. (For oak use a grain nr. 150, for pine you can use nr. 220). Should it be necessary the exposed wood can be stained prior to waxing using either a water-based or oil-based stain, but this must be allowed to thoroughly dry before wax is applied.

**APPLICATION:**

Using a soft cloth, brush, or pad (which will not damage the surface of the finish), apply wax directly to the surface of the wood using light, circular motions. Apply sparingly, using just enough to coat the wood. Wax should be applied going against the grain. In hard-to-reach areas (like spindles, carved areas, and etc.) use cut-up rags, special pads, foam paint brushes, or smaller pieces then allow waxed wood to set naturally. Wax should remain on furniture or other wood for a minimum of 5-7 minutes. Buff wood using a clean, soft cloth. On carved or detailed areas of furniture, you may need to use a furniture brush or similar object to buff the area. Apply a second coat of wax with a soft, clean rag, this time working with the grain of the wood. Again, use circular motions and apply only a thin layer of wax, making sure all areas are covered equally. Allow wax to set for 60-75 minutes. Once buffing is done, allow wood to sit overnight. Use a clean rag to buff the wood once more, paying special attention to corners, hard-to-reach areas and blemishes. Note: The more layers of wax that are applied and buffed, the more glossy your furniture's finish will become. After using a wax treatment it is not recommended to use a conventional varnish system unless the wood can be completely stripped back and be free of all wax coatings.

**COVERAGE:**

Depending on surface texture and tile porosity, coverage is 80-140 gr./ square metres equivalent to about 3.5 to 6 of surface per 500gm pack for a single coat application.

**HEALTH & SAFETY PRECAUTIONS:**

**Flammable liquid and vapour. Toxic to aquatic life with long lasting effects. Causes damage to organs Central nervous system through prolonged or repeated exposure if inhaled. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do NOT induce vomiting. IF SWALLOWED: Immediately call a doctor / NHS Direct. IF ON SKIN: Wash with plenty of soap and water. Do not breathe vapours. IF INHALED: Remove victim to fresh air and keep in a position comfortable for breathing. Do not get in eyes, on skin, or on clothing. IF ON SKIN Remove immediately all contaminated clothing. Rinse skin with water/shower. Store in a well-ventilated place. Keep container tightly closed Keep cool.

**STORAGE & PACKAGING:**

LANGLOW WAX POLISH is packed in 500gm steel cans and is suitable for use in TROPICAL climates where temperatures may be above 30°C. In its' sealed state the wax has a shelf life of 2 years when stored at ambient temperatures.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.