



TECHNICAL DATA SHEET



Ver 03 - PALWCA 11.02.22

WALLCOVERING ADHESIVE

READY MIXED WALL-COVERING ADHESIVE FOR VINYL

- EXCELLENT INITIAL GRAB
- FIXES ALL TYPES OF WALL COVERING
- DRIES TO A CLEAR SECURE BOND
- FOR VINYL WALL COVERINGS
- CONTAINS A FUNGICIDAL PRESERVATIVE



PALACE RM WALL-COVERING ADHESIVE

Is ready mixed for immediate use and is suitable for hanging vinyl wall-coverings including heavy-duty paper or fabric backed types, hessians, expanded polystyrene veneer and blow vinyl to all suitably prepared wall surfaces. This product contains a fungicidal preservative.

EXCELLENT
GRAB

FIXES TO ALL TYPE OF
WALL COVERINGS



EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

PALACE CHEMICALS LTD

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 - FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK

WALLCOVERING ADHESIVE

Ready Mixed Wall-Covering Adhesive for Vinyl



DESCRIPTION

PALACE READY MIXED WALL-COVERING ADHESIVE is ready mixed for immediate use and is suitable for hanging vinyl wall-coverings including heavy-duty paper or fabric backed types, hessians, expanded polystyrene veneer and blow vinyl to all suitably prepared wall surfaces. This product contains a fungicidal preservative.

SURFACE PREPARATION

Surfaces to be covered should be clean, dry & dust free. Highly absorbent walls should be primed with a dilution of 1 part adhesive to 1 part water to stabilise the surface. The priming coat must be allowed to dry before commencing hanging. Do not use this product at temperatures below 10°C.

APPLICATION METHOD

Apply the adhesive liberally by brush or roller onto paper-backed wall-coverings and hang in the normal way to ensure the pattern continuity is maintained from strip to strip. For other types of wall-covering such as polystyrene veneers and Novamura, spread the adhesive directly to the wall and then hang the wall-covering. If any adhesive gets on the decorative surface of the wall-covering, remove immediately with a damp cloth. For paper backed HESSIAN the adhesive should be applied to the paper backing however on bare hessians always apply the adhesive to the wall. Clean tools immediately in water after use.

COVERAGE

Approximately 5.5 sq. metres per kg.

STORAGE AND PACKAGING

READY MIXED WALL-COVERING ADHESIVE is supplied in 1 litre; 2.5 litre & 5 litre tubs and has a storage life of not less than 12 months if kept in dry, un-opened conditions away from frost or elevated temperatures (> 35°C).

HEALTH AND SAFETY

A complete PALACE material safety data sheet is available on request or online at www.palacechemicals.co.uk

QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at: <http://www.palacechemicals.co.uk>

DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate, however it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.



EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

PALACE CHEMICALS LTD

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 – FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK