

Ver 03 - PALWAL 10.02.22

WALLPAPER PASTE

ALL PURPOSE STARCH BASED SOLUBLE FLAKE

- COLF WATER SOLUBLE
- EASY TO DISPERSE
- BRUSHES ON NON-DRIP
- HANGS UP TO 5 ROLLS PER MIXED GALLON
- CONTAINS A PROTECTIVE BIOCID



PALACE WALLPAPER PASTE

Is a traditional starch based water soluble flake suitable for hanging all types of vinyl wall-coverings including textured papers, anaglypta and blow vinyl to all suitably prepared wall surfaces. This product contains a fungicidal preservative to prevent black spot mould.

SUITABLE FOR ALL TYPES OF VINYL COVERINGS

AVAILABLE IN 3 SIZES

WALLPAPER PASTE

All Purpose Starch Based Soluble Flake



DESCRIPTION

PALACE ALL-PURPOSE WALLPAPER PASTE is a traditional, easy to mix starch flake type product, containing chemically incorporated anti-mould additives. With excellent easy slip properties, it may be used for all wallpapers including woodchip, washables, vinyls and heavily embossed. Also ideal for applying polystyrene tiles and for use as a size for sealing new plaster walls prior to papering.

SURFACE PREPARATION

Surfaces to be covered should be clean, dry & dust free. Highly absorbent walls should be primed with a dilution of 1:1 (adhesive:water) to stabilise the surface. The priming coat must be allowed to dry before commencing hanging. Do not use this product at temperatures below 10°C.

MIXING

The volume of cold water to use to make the mix appropriate to the type of paper is given as a rough guide by the table below. Sprinkle contents of sachet into water stirring quickly for 30 seconds to disperse, then when mixed to a smooth lump-free paste leave to stand for 3 minutes then stir again thoroughly. The paste is then ready to use.

HEALTH AND SAFETY

A complete PALACE material safety data sheet is available on request or online at www.palacechemicals.co.uk

QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at:
<http://www.palacechemicals.co.uk>

DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate, however it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

MIXING RATIOS

APPLICATION NORMAL WALLPAPERS INCLUDING WOODCHIP

WATER TO USE PER SACHET 6 pints / 3.5 litres

APPROXIMATE COVERAGE 4 - 5 rolls

APPLICATION VINYL WALLCOVERINGS, WASHABLE & NOVAMURA

WATER TO USE PER SACHET 5 pints / 3 litres

APPROXIMATE COVERAGE 4 rolls

APPLICATION BLOWN VINYL WALLCOVERINGS

WATER TO USE PER SACHET 5 pints / 3 litres

APPROXIMATE COVERAGE 4 rolls

APPLICATION EMBOSSED PAPERS (ANAGLYPTA)

WATER TO USE PER SACHET 4 pints / 2.5 litres

APPROXIMATE COVERAGE 2 - 2½ rolls

APPLICATION HEAVY EMBOSSED PAPERS (SUPAGLYPTA)

WATER TO USE PER SACHET 3.5 pints / 3 litres

APPROXIMATE COVERAGE 1¾ - 2 rolls

APPLICATION POLYSTYRENE TILES

WATER TO USE PER SACHET 4 pints / 2.5 litres

APPROXIMATE COVERAGE 80 sq ft - 20m²



EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

PALACE CHEMICALS LTD

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 - FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK