



## **Declaration of Performance**

**No. DS 681 CPR 11-06-14**

1.) Unique identification code of the product type

**Laticret SPECTRA-LOCK PRO Premium Grout**

2.) Type, batch or serial number or any other element allowing identification of the construction product

**DS 681.0-1114**

3.) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer.

**Reaction Resin Tile Grout**

4.) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under article (11)5:

**LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA**

5.) Where applicable, the name and contact address of an authorized representative may be stated

6.) System of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7.) In the case of the declaration of performance concerning a construction product covered by the harmonized standard

**EN 13888:2009 – RG**

**The Notified Body Lucideon (Previously Named Ceram) NB 1289 performed the Initial Type Testing  
under system 3 and issued the following report:**

**Test report (145324)-26356**





8) Declared Performance

Essential characteristics	Performance	Harmonised technical specification
<b>Compressive strength as:</b> <ul style="list-style-type: none"> <li>Compressive strength EN12808-3</li> </ul> <b>Flexural strength as:</b> <ul style="list-style-type: none"> <li>Flexural strength EN12808-3</li> </ul> <b>Abrasion resistance:</b> <ul style="list-style-type: none"> <li>Resistance to abrasion EN 12808-2</li> </ul> <b>Water absorption:</b> <ul style="list-style-type: none"> <li>Tested as per EN 12808-5</li> </ul> <b>Shrinkage:</b> <ul style="list-style-type: none"> <li>Tested as per EN 12808-4</li> </ul> <b>Reaction to Fire</b>	<p>&gt; 45.0 N/mm<sup>2</sup></p> <p>&gt; 30.0 N/mm<sup>2</sup></p> <p>&lt; 250mm<sup>3</sup></p> <p>&lt; 0.1g after 6 hours</p> <p>&lt; 1.5mm/m</p> <p>NPD</p>	<p><b>EN 13888:2009</b></p>
<b>Release of dangerous substances</b>	<b>See MSDS</b>	

9) The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 8 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by:

Jim Percival – Technical Director Laticrete UK

On 1<sup>2th</sup> November 2014

Laticrete International, Inc 1 LATICRETE Park North, Bethany, CT 06524-3423 USA

**Globally Proven Construction Solutions**

