



## **Declaration of Performance**

**No. DS 633 CPR 04-04-14**

1.) Unique identification code of the product type

**Latcrete PLATINUM 254 (Grey)**

2.) Type, batch or serial number or any other element allowing identification of the construction product

**DS 677.0-0414**

3.) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer.

**Cementitious thin bed standard setting tile & stone adhesive**

4.) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under article (11)5:

**LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA**

5.) Where applicable, the name and contact address of an authorized representative may be stated

6.) System of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7.) In the case of the declaration of performance concerning a construction product covered by the harmonized standard

**EN 12004:2007 + A1:2012 – C2TE-S2**

**The Notified Body Lucideon (Previously Named Ceram) NB 1289 performed the Initial Type Testing under system 3 and issued the following report:**

**Test report (141610)-7308**





8) Declared Performance

Essential characteristics	Performance	Harmonised technical specification
<b>Bond strengths as:</b> <ul style="list-style-type: none"> <li>Initial tensile adhesion strength -</li> <li>Initial tensile adhesion strength – after water immersion</li> <li>Initial tensile adhesion strength – after heat aging</li> <li>Initial tensile adhesion strength – after freeze/thaw cycles</li> </ul>	> 1.0 N/mm <sup>2</sup> > 1.0 N/mm <sup>2</sup> > 1.0 N/mm <sup>2</sup> > 1.0 N/mm <sup>2</sup>	<b>EN 12004:2007 + A1:2012</b>
<b>Open time tensile adhesion strength:</b> <ul style="list-style-type: none"> <li>Tensile strength after 30 minutes open time</li> </ul>	> 0.5 N/mm <sup>2</sup>	
<b>Traverse Deformation:</b> <ul style="list-style-type: none"> <li>Deformation (EN 12002)</li> </ul>	> 5.0 mm	
<b>Reaction to Fire</b>	NPD	
<b>Reduced Slip</b>	< 0.5mm	
<b>Release of dangerous substances</b>	See MSDS	

9) The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 8 under the sole responsibility of the manufacturer identified above.

**Signed for & on behalf of the manufacturer by:**

Sean Boyle, Director. Marketing & Product management

On 1<sup>st</sup> October 2014

Laticrete International, Inc 1 LATICRETE Park North, Bethany, CT 06524-3423 USA

**Globally Proven Construction Solutions**

