



No. 0335R-0050-21/ 1-CPR/2013
DECLARATION OF PERFORMANCE

1. Unique identification code of the product type:
LATICRETE 335R SUPER-FLEX
2. Batch / serial No. identifying the construction product as required under Article 11(4)
NB. Batch number is printed on the side of the bag with date of manufacture.
3. Intended use in accordance with the harmonised standard:
Improved fast setting & deformable cementitious adhesive with extended open time & reduced slip for internal & external tiling
4. Name & contact address of the Manufacturer:
**Laticrete UK Ltd
 Speke Hall Industrial Estate; Speke; Liverpool
 L24 1YA**
5. Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)
Not applicable
6. System of assessment & verification of constancy of performance as set out in Annex V:
System 3
7. Harmonised EN Standard:
EN 12004:2007 + A1:2012
**The notified body No. NB1289 CERAM (LUCIDEON) performed the test according to EN 12004:2007 + A1:2012 under system 3 and issued the following report:
 Test report (104751)-22375.**
8. Declared Performance:
To harmonised technical specification: EN 12004:2007 + A1:2012

Essential characteristics	Performance	Harmonised technical specification
Bond strength as: <ul style="list-style-type: none"> • Early tensile adhesion strength • Initial Tensile adhesion strength 	> 0.5 N/mm ² > 1.0 N/mm ²	EN 12004:2007 + A1:2012
Extended open time tensile adhesion strength: <ul style="list-style-type: none"> • Tensile strength after 30 minutes open time 	> 0.5 N/mm ²	
Durability for: <ul style="list-style-type: none"> • Tensile adhesion strength after heat ageing • Tensile adhesion strength after freeze thaw cycles • Tensile adhesion strength after water immersion 	> 1.0 N/mm ² > 1.0 N/mm ² > 1.0 N/mm ²	
Reduced Slip	< 0.5mm	
Deformable adhesive	>2.5mm	
Reaction to Fire	Class F	
Release of dangerous substances	See MSDS	

9. Declaration:
The performance of the above product identified in points 1 & 2 is in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued by the manufacturer identified in point 4

Signed for & behalf of
 Laticrete Ltd:

Jim Percival - Technical Director – Laticrete UK Ltd

Date: 24th March 2014



LATICRETE UK Ltd
 Speke Hall Industrial Estate;
 Speke; Liverpool; L24 4AB
 Tel: 0151 486 6101 – Fax: 0151 448 1982
 e-mail: jp@laticrete.co.uk

