



Ref: 134P - FLOW LEVEL 2-part FLOOR LEVELLING compound 0918

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY:

1.1 Product Name: FLOW LEVEL smooth floor leveller

1.2 Applications: Levelling uneven concrete & masonry floors

1.3 Supplier: Palace Chemicals Ltd; Speke Hall Industrial Estate; Speke; Liverpool; L24 1YA

Tel: 0151 486 6101; Fax 0151 448 1982

e-mail: sales@palacechemicals.co.uk; web: www.palacechemicals.co.uk

1.4 Emergency Telephone No. Tel: 0151 486 6101; Fax 0151 448 1982; e-mail:jp@palacechemicals.co.uk

2. HAZARDS IDENTIFICATION:

2.1 Classifications:

(EC) No. 1272/2008 Skin Irritant. 2; H315 - Skin Sens Cat 1; H317

Hazard phrases: H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

DANGER

Signal word: P102 Keep out of reach of children.

P260a Do not breathe dust.

Precautionary phrases: P280f Wear protective gloves, eye and face protection.

P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P501a Dispose of contents/container in accordance with local regulations.

2.2 Other hazards: Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.

Contact between cement powder and body fluids. Contains Calcium oxide. When mixed with water it

will form calcium hydroxide which has a corrosive effect on skin and eves.

If stored correctly and used within 12 months of the date shown on this bag, the activity of the reducing agent will be maintained and this product will contain, when mixed, no more than 0.0002 % (2 ppm) soluble chromium (VI) of the total dry weight of the cement. Use of this product after the end

of the declared storage period may increase the risk of an allergic reaction.

3. COMPOSITION / INFORMATION ON INGREDIENTS:

3.1 Substances: N/A

3.2 Mixtures: Blends of cements; hydraulic binders; plasticisers and graded silica sands

Name:	CAS No.:	EINECS:	Concentration:	Classification:
Portland Cement:	65997-15-1	266-043-4	< 3.0% w/w	H315; H318; H317; H335
Hydrated lime	1305-62-0	215-137-3	1.00 – 5.00 % w/w	H315; H318; H335
Silica Sand	14808-60-7	238-878-4	40.0 – 60.0 % w/w	n/a







4. FIRST AID MEASURES:

4.1 Description of measures:

EYE CONTACT: Do not rub eye. Immediately flush with plenty of water for up to 15 minutes. Remove any contact

lenses and open eyelids. If irritation persists: Continue flushing during transport to hospital.

INHALATION: Remove affected person to fresh air. If nose or airways become inflamed or breathing difficulties

occur and irritation persists seek medical attention.

SKIN CONTACT: Remove contaminated clothing immediately and wash skin with soap and water.

In case of rashes, wounds or other skin disorders: Seek medical attention.

INGESTION: Clean out mouth with copious volumes of water and drink plenty. Do not induce vomiting. Seek

medical attention if mouth is inflamed.

4.2 Acute & Chronic symptoms:

Inhalation: Frequent inhalation of large quantities of cement dust over a long period of time increases the

risk of developing lung diseases. Dust may irritate throat and respiratory system and cause coughing. Frequent inhalation of dust over a long period of time increases the risk of developing

lung diseases.

Ingestion: Unlikely route of entry

Skin contact: Cement may have an irritating effect on moist skin (due to transpiration or humidity) after

prolonged contact. Prolonged skin contact with wet cement or fresh concrete may cause serious burns because they develop without pain being felt (for example when kneeling in fresh concrete even when wearing trousers). Repeated skin contact with wet cement may cause

contact dermatitis.

Eye Contact: Eye contact with cement (dry or wet) may cause serious and potentially irreversible injuries.

4.3 Immediate medical attention: See First Aid measures above

5. FIRE FIGHTING MEASURES:

5.1 Extinguishing media: All cement-based blends are non-flammable, although paper sacks may well smoulder &

combust. Use extinguisher appropriate to the surrounding materials & fire.

5.2 Combustion Hazards: Oxides of carbon and paper ash.

5.3 Advice for fire-fighters: None applicable

6. ACCIDENTAL RELEASE MEASURES:

6.1 Personal protection: Avoid inhalation of dust. Avoid contact with eyes and prolonged skin contact. Use work methods

which minimise dust production.

6.2 Environmental precautions: Contain spillage within a defined area and avoid discharge to watercourses and drains

6.3 Spill removal methods: Ideally use an industrial vacuum cleaner and only brush residues when sprinkled with a

dampened absorbent (sawdust or granules) into sealable containers when wearing personal

protective equipment and ensuring adequate ventilation is available

6.4 References to other sections: Before attempting any clean-up operation, consult the requirements for protective equipment

shown in section 8 of this document.

7. HANDLING & STORAGE:

7.1 Safe handling precautions: Lifting operations of no more than 1 x 20kg sack at a time by a competent operator wearing.

7.2 (a) Safe storage conditions: Store in sealed, clearly marked sacks. Keep out of reach of children in a cool well-ventilated

environment, preferably off the ground and out of contact with water. This product must be stored in unopened bags in cool dry conditions and protected from excessive draught.

7.2 (b) Incompatible materials: Avoid exposure to moisture when in storage prior to use

7.3 Specific storage conditions: Keep in sealed packaging off the ground and away from contact with moisture.





8. EXPOSURE CONTROLS & PERSONAL PROTECTION:

8.1 Control parameters

Substance: 8 hour exposure limit Type: Source:

Portland Cement dust: 4mg/M3 TWA EH40

Respirable

Portland Cement dust: 10mg/M3 TWA EH40

Inhalable

8.2 Exposure controls:

Engineering controls: Provide adequate ventilation. Observe occupational exposure limits and minimise the risk of

inhalation of dust by using contained ventilation where practical.

Respiratory protections: During dust-raising work: Use respiratory equipment with particle filter, type

P2. Or wear a BS rated disposable dust mask for each daily task.

Hand protection: Wear heavy duty natural rubber gloves or gauntlets approved to EN 374 &

EN 420 with a BTT rating of > 8 hrs for strong alkalis.

Eye protection: Dust proof BS 2092 Goggles or chemical grade visors are also advised

wherever there is a risk of dust or paste entering the eyes.

Other Protection: PVC overalls with elasticated cuffs and closed neck should be worn and

laundered immediately after use. Do not work in powder or paste contaminated overalls. skin care products (including barrier creams) to protect the skin from prolonged contact with wet cement. Particular care should be taken to ensure that wet cement does not enter the boots. In some circumstances such as when laying concrete or screed, waterproof trousers

or Knee-pads are necessary.

Hygiene measures: Contact with skin must be washed off immediately











9. PHYSICAL & CHEMICAL PROPERTIES:

Appearance: Coarse grey powder **Dry bulk density**: 1100 g/ltr

Odour: Negligible Wet Bulk Density: 1800 g/ltr +/- 100

Odour threshold: n/a Solubility in oils: Insoluble pH: >11.0 when mixed Water solubility: Insoluble

Flash point: n/a

Melting point: n/a

Boiling point: n/a

Mento-ignition temperature: n/a

Decomposition temperature: n/a

Surface tension: n/a

Evaporation rate: n/a Viscosity: n/d
Upper/Lower Flam limits: n/a Explosive properties: Nil
Vapour pressure: n/a Oxidising properties: Nil

Vapour density: n/a Particle size: 50 to 1000 micron

10. STABILITY & REACTIVITY:

10.1 Conditions to avoid: Humidity & moisture during storage **10.4 Reactivity:** Stable

10.2 Incompatible Materials:Not known10.5 Chemical reactivity:Aqueous media10.3 Decomposition hazards:Stable10.6 Risk of hazardous reaction:Not known





11. TOXICOLOGICAL INFORMATION:

11.1 Information on toxicological effects: This product has not been exhaustively tested. Judgements on the expected toxicity of this product have been made based upon consideration of its' major components.

Routes of exposure:

Inhalation, ingestion & contact with skin & eyes all have the potential for adverse effects on human organs when subject to acute and chronic levels of exposure. Chronic exposure to respirable dust in excess of occupational exposure limits may cause coughing, shortness of breath and may cause chronic obstructive lung disease (COPD).

Eye damage/irritation:

Direct contact with dry cement may cause corneal damage by mechanical stress, i or delayed irritation. Direct contact by larger amounts of dry cement or splashes of wet cement may cause effects ranging from moderate eye irritation to chemical burns and blindness.

Skin Corrosivity / Irritation:

Some individuals may exhibit eczema upon exposure to wet cement, caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis [Reference (4)]. As this product contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness of the chromate reduction is not exceeded, a sensitising effect is unlikely

Respiratory/skin sensitisation:

Dry cement in contact with wet skin or exposure to moist or wet cement may cause thickening, cracking or fissuring of the skin. Prolonged contact in combination with abrasion can cause severe burns.

12. ECOLOGICAL INFORMATION:

12.1 Ecotoxicity: The product is not expected **12.4 Mobility in soil:** negligible

to be hazardous to the

environment.

12.2 Bio-accumulative potential: Not relevant

12.3 Persistence & degradability: After hardening, cement

presents no toxicity risks.

12.5 PBT and vPvB result: Not relevant

12.6 Other adverse effects: Avoid contamination of

watercourses as risks increasing alkalinity

13. DISPOSAL CONSIDERATIONS:

13.1 Waste treatment Methods: To be disposed in accordance with local authority regulations for builders waste

Allow to harden, avoid entry in sewage and drainage systems or into bodies of water (e.g., streams) and dispose of according to the local legislation. Avoid entry into the sewage water system. Dispose of the hardened product as concrete waste. Due to the inertisation, concrete

waste is not classed as a dangerous waste.

14. TRANSPORT INFORMATION:

Transport Labels:

Cement based dry-pack mortars of this type are not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID) and therefore no classification is required.

Regulatory Code (Land, Sea & Air):	ADR	IMDG	ICAO	
14.1 UN No.:				
14.2 Proper shipping name:				
14.3 ADR Packing Group:				
14.4 Transport Hazard Class:				
14.5 Environmental hazards.				
14.6 Special user precautions:				
14.7 Transport in bulk – IBC code:			·	

15. REGULATORY INFORMATION:

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

All components are listed as existing substances in Europe

UK Regulatory References:

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Environmental Listing - Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

Statutory Instruments:

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.



MATERIAL SAFETY DATA SHEET VERSION 1 - DPD / 1999 / 45 / EEC



Guidance Notes:

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

EU Legislation:

Dangerous Substance Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European

Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC,

National Regulations:

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.

Authorisations (Title VII Regulation 1907/2006) - No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) - No specific restrictions of use are noted for this product.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this product.

16. OTHER INFORMATION:

Last revision date: 07/09/18

SDS No.: 134P

List of abbreviations used in this SDS:

CAS Chemical abstracts service

CLP Classification, labelling & packaging regulation (EC) No. 1272/2008

DSD Dangerous substances Directive 67/548/EEC
DPD Dangerous Products Directive 1999/45/EC
PBT Persistent, Bio-accumulative & Toxic

REACH Registration, Evaluation, Authorisation & Restriction of Chemicals Regulation (EC) 1907/2006

Volume VII Approved supply list; EH40; Croner; Supplier RM safety data sheets

vPvB Very Persistent, very Bio-accumulative

ation methods:

Classification methods:

References:

H phrases in section 2: H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation H335 May cause respiratory irritation.

Precautionary phrases: P102 Keep out of reach of children.

P260a Do not breathe dust.

P280f Wear protective gloves, eye and face protection.

P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P501a Dispose of contents/container in accordance with local regulations.

Training for workers:

Disclaimer: The information supplied in this safety data sheet is intended to assist in the use of the above product without risk to safety

and health and is based on current knowledge and experience of the associated physico-chemical hazards. The data does not signify any warranty with regard to the product's properties. This information may be used to assist in formulating a

COSHH risk assessment if applied at work. This data sheet complies with EC Directive 91/155EC.





Ref: 134 / FLOW LEVEL - FLOOR SCREED Latex

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY:

1.2 Product name & codes: FLOOR SCREED LATEX additive

1.2 Applications: Additive for mixing only with FLOW LEVEL-part powder floor leveller

1.3 Supplier: Palace Chemicals Ltd; Speke Hall Industrial Estate; Speke; Liverpool; L24 1YA

Tel: 0151 486 6101; Fax 0151 448 1982

e-mail: sales@palacechemicals.co.uk; web: www.palacechemicals.co.uk

1.4 Emergency Telephone No. Tel: 0151 486 6101; Fax 0151 448 1982; e-mail:jp@palacechemicals.co.uk

2. HAZARDS IDENTIFICATION:

2.1 Classifications:

(EC) No. 1272/2008 Not Classified **Hazard phrases:** None applicable

Signal word: None Applicable

Precautionary phrases: P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective clothing, gloves, eye and face protection.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

2.2 Other hazards: None applicable

3. COMPOSITION / INFORMATION ON INGREDIENTS:

3.1 Substances: No hazardous materials present at a level which requires the product to be classified.

3.2 Mixtures: Water based dispersion of styrene acrylic copolymer.

Name:	CAS No.:	EINECS:	Concentration:	Classification:
Styrene acrylate copolymer	polymeric		30 - 50.0% w/w	N/A
1,2-benzisothiazol-3(2H)-one	2634-33-5	220-088-00-6	< 50ppm	H318, H400, H411, H302,H315, H317
2-methylisothiazol-3(2H)-one	2682-20-4	220-239-6	< 50ppm	H301,H330, H318, H314, H400, H411, H317

4. FIRST AID MEASURES:

4.1 Description of measures:

EYE CONTACT: Immediately wash out the eyes with plenty of water. Seek medical attention if symptoms persist

INHALATION: Remove from exposure. Keep warm and rest.

SKIN CONTACT: Wash the skin with soap and water

INGESTION: Wash out the mouth with water. Do not induce vomiting. Seek medical attention if large amounts

ingested

4.2 Acute & Chronic symptoms:

Inhalation: None Ingestion: None Skin contact: None

Eye Contact: Eye contact with mixed paste may cause pro-longed irritation.

4.3 Immediate medical attention: See First Aid measures above





5. FIRE FIGHTING MEASURES:

5.1 Extinguishing media: Use extinguisher appropriate to the surrounding materials & fire.

5.2 Combustion Hazards: Outer polypropylene packaging is combustible in direct contact with flame.

5.3 Advice for fire-fighters: Self contained breathing apparatus should be worn.

6. ACCIDENTAL RELEASE MEASURES:

6.1 Personal protection: Wear impervious gloves, overalls, eye protection while clearing up the spillage.

6.2 Environmental precautions: Contain and collect the spillage. Do not wash into drains.

6.3 Spill removal methods: Shovel up excess paste then promptly wash surface residues with water.

6.4 References to other sections: Before attempting any clean-up operation, consult the requirements for protective equipment

shown in section 8 of this document.

7. HANDLING & STORAGE:

7.1 Safe handling precautions: Handle in accordance with good safety and hygiene practices. Avoid spillages as the wet paste

will be slippery underfoot. Use in a well-ventilated area.

7.2 (a) Safe storage conditions: Store in sealed, clearly marked buckets. Keep out of reach of children in a cool well-ventilated

environment.. This product must be stored in in cool dry conditions and protected from extreme

temperatures (keep at +5'C to 35'C).

7.2 (b) Incompatible materials: Avoid exposure to moisture when in storage prior to use

7.3 Specific storage conditions: None applicable

8. EXPOSURE CONTROLS & PERSONAL PROTECTION:

8.1 Control parameters

Substance: 8 hour exposure limit Type: Source:

None applicable

8.2 Exposure controls:

Engineering controls: Provide adequate ventilation.

Respiratory protections: Dust masks may be required if the product is handled roughly

Hand protection: Impervious gloves may be needed for sensitised individuals

Eye protection: Goggles may be required if the product is handled roughly

Other Protection: PVC overalls may be worn and should be laundered immediately after use.

Hygiene measures: Contact with skin must be washed off immediately

9. PHYSICAL & CHEMICAL PROPERTIES:

Appearance: White liquid Dry bulk density: n/a

Odour: Feint acrylic Wet Bulk Density: 1030 g/ltr +/- 20 Solubility in oils: Odour threshold: n/a Insoluble pH: 6.0 - 8.0Water solubility: Complete Flash point: Auto-ignition temperature: n/a n/a

Melting point:n/aDecomposition temperature:n/aBoiling point:n/aSurface tension:n/a

Evaporation rate: n/a **Viscosity:** 200 – 800 mPa.s

Upper/Lower Flam limits:n/aExplosive properties:NilVapour pressure:n/aOxidising properties:NilVapour density:n/aParticle size:n/a





10. STABILITY & REACTIVITY:

10.1 Conditions to avoid: Extreme temperatures 10.4 Reactivity: Stable

10.2 Incompatible Materials:Not known10.5 Chemical reactivity:Aqueous media10.3 Decomposition hazards:Stable10.6 Risk of hazardous reaction:Not known

11. TOXICOLOGICAL INFORMATION:

11.1 Information on toxicological effects: This product has not been exhaustively tested. Judgements on the expected toxicity of this product have been made based upon consideration of its' major components.

Routes of exposure:

Ingestion & contact with skin & eyes

Eye damage/irritation:

Direct contact with wet paste may cause eye irritation if unattended.

Skin Corrosivity / Irritation:

None

Respiratory/skin sensitisation:

None known

12. ECOLOGICAL INFORMATION:

12.1 Ecotoxicity:Not hazardous to the environment.12.4 Mobility in soil:negligible12.2 Bio-accumulative potential:Not relevant12.5 PBT and vPvB result:Not relevant12.3 Persistence & degradability:Partially biodegradable.12.6 Other adverse effects:Not relevant

13. DISPOSAL CONSIDERATIONS:

13.1 Waste treatment Methods: To be disposed in accordance with local authority regulations for non-hazardous builders waste.

Existing EEC, National and Local Regulations must always be complied with.

14. TRANSPORT INFORMATION:

Transport Labels:

This product is **not covered** by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID) and therefore no classification is required.

Regulatory Code (Land, Sea & Air):	ADR	IMDG	ICAO	
14.1 UN No.:				
14.2 Proper shipping name:				
14.3 ADR Packing Group:				
14.4 Transport Hazard Class:				
14.5 Environmental hazards.				
14.6 Special user precautions:				
14.7 Transport in bulk – IBC code:			<u>.</u>	

15. REGULATORY INFORMATION:

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

All components are listed as existing substances in Europe

UK Regulatory References:

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Environmental Listing - Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

Statutory Instruments:

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.





EU Legislation:

Dangerous Substance Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European

Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC,

National Regulations:

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.

Authorisations (Title VII Regulation 1907/2006) - No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) - No specific restrictions of use are noted for this product.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this product.

16. OTHER INFORMATION:

Last revision date: 07-09-18

SDS No.: 134L

References: Volume VII Approved supply list; EH40; Croner; Supplier RM safety data sheets

Classification methods:

:

H phrases in section 2:

Precautionary phrases: P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective clothing, gloves, eye and face protection.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Training for workers:

Disclaimer: The information supplied in this safety data sheet is intended to assist in the use of the above product without risk to safety

and health and is based on current knowledge and experience of the associated physico-chemical hazards. The data does not signify any warranty with regard to the product's properties. This information may be used to assist in formulating a

COSHH risk assessment if applied at work. This data sheet complies with EC Directive 91/155EC.