



DECLARATION OF PERFORMANCE

No. 47-26 / 1-CPR/2013

Identification: **FLEXI-SET POURABLE THICK BED ADHESIVE (47-26)**
Ceramic & Stone tile adhesive for large tiles and on uneven floors
NB. Batch number is printed on the side of the bag with date of manufacture.

Intended use: Fast setting improved cementitious adhesive with extended open time for internal & external tiling

Manufacturer: PALACE CHEMICALS Ltd
Speke Hall Industrial Estate
Speke
Liverpool
L24 1YA
Tel: 0151 486 6101
Fax: 0151 448 1982
www.palacechemicals.co.uk

System of assessment: System 3

Harmonised EN Standard: EN 12004:2007 + A1:2012

Notified Body: The notified body No. NB1289 carried out the determination of the product-type on the basis of type testing on samples taken by the manufacturer under system 3 and issued the test report (124269)-17278.

Declared Performance: To harmonised technical specification: **EN 12004:2007 + A1:2012 – C2FE**

Early Tensile adhesion strength	> 0.5 N/mm ²
Initial Tensile adhesion strength	> 1.0 N/mm ²
Tensile strength after 30 minutes open time	> 0.5 N/mm ²
Tensile adhesion strength after heat ageing	> 1.0 N/mm ²
Tensile adhesion strength after freeze thaw cycles	> 1.0 N/mm ²
Tensile adhesion strength after water immersion	> 1.0 N/mm ²
Reaction to Fire	Class F
Release of dangerous substances	See MSDS

Declaration: The performance of the above product in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued under the sole responsibility of Palace Chemicals Ltd.

Signed for & behalf of
Palace Chemicals Ltd:

Jim Percival

Technical Director – Palace Chemicals Ltd



PALACE CHEMICALS Ltd

Speke Hall Industrial Estate;
Speke; Liverpool; L24 4AB
Tel: 0151 486 6101 – Fax: 0151 448 1982
e-mail: sales@palacechemicals.co.uk

Registered No. 1377341 England

