



TECHNICAL DATA SHEET

DEC 2025 Ver 01 - PALGFM 01.12.25



GROUT & CEMENT FILM REMOVER

FROM TILE FACES & GROUT JOINTS

- Removes efflorescence
- Lifts & dissolves difficult stains
- Softens & removes cement film
- Ideal for glazed quarry tiles, brick & acid resistant surfaces

DESCRIPTION

PALACE GROUT & CEMENT FILM REMOVER is designed for use on any non-calcareous tiled surface, which is resistant to acid attack. **PALACE GROUT & CEMENT FILM REMOVER** solution is designed to quickly, effectively and safely remove grout, adhesive residue, and cement films from floors.

APPLICATION

To ensure the tiled surface is not acid sensitive, test-apply a few drops to a small innocuous area. If no reaction or permanent surface discoloration is observed then dilute **PALACE GROUT & CEMENT FILM REMOVER** 1:7 parts with water and spread the solution across a pre-wet surface. Apply liberally, covering no more than 10 - 15 m² at a time. Where hardened cement film has accumulated, apply mild abrasion to the area. **PALACE GROUT & CEMENT FILM REMOVER** should only be used neat where heavy cement deposits have built up. Allow the solution to work for around 10 minutes, then rinse well with clean water at least 2-3 times with a mop and bucket. If necessary, repeat the application locally where any residual stains remain.

TECHNICAL DATA

UNIT SIZE	1L
CONSISTENCY	Liquid
COLOUR	Transparent
DENSITY	1.07g/cm ³
PH	1.5
APPLICATION TEMPERATURES	0 - 40°C
WAIT TIME BEFORE RINSING	5 Minutes

EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

📍 Speke Hall Industrial Estate, Speke, Liverpool, L24 1YA
☎ +44 (0) 151 336 9104 @ sales@palacechemicals.co.uk
🌐 www.palacechemicals.co.uk
Registered No. 1377241 England



TECHNICAL DATA SHEET

DEC 2025 Ver 01 - PALGFM 01.12.25

COVERAGE

When diluted, this product will cover up to 10 square metres per litre, depending on surface texture and the degree of staining to be removed. **WARNING: Grout Film Remover should not be used on Calcareous Natural Stone, Travertine, Marble, Slate, Terrazzo, Granito, Cementitious tiles and any other acid sensitive surfaces.**

STORAGE

Store in cool, dry, well-ventilated conditions, away from sources of heat, direct sunlight or exposure to frost. Always completely reseal the container after partial use. Keep away from Children.

PROPERTIES

PALACE GROUT & CEMENT FILM REMOVER is designed for use on any non-calcareous tiled surfaces which are resistant to acid attack. This product is a blend of non-ionic surfactants, inorganic acids and sequestering agents designed to lift cement-based film, lime-scale and efflorescent residues from the surface and leave a clean bare tiled surface finish which may then be further treated with an appropriately selected surface protective sealer.

HEALTH & SAFETY

Causes severe skin burns and eye damage.

Keep locked up and out of the reach of children.

Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with water and seek medical attention.

Remove and launder all contaminated clothing. Do not empty directly into drains or watercourses. Wear suitable gloves, eye / face protection, PVC overalls and rubber boots when in use. If swallowed seek medical advice immediately and show this label. Take off contaminated clothing & wash before reuse. Contains: 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.



QUALITY & ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

TECHNICAL ADVICE

Should further technical information be required, call the Palace Chemicals Technical Helpline on 0151 336 9104.

DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or control over where and how our products are stored and used. All products are sold and guaranteed subject to our terms and conditions of sale, copies of which may be obtained on request.

EXTENSIVE PRODUCT RANGE

We offer the most extensive range of Tiling & Flooring products in the UK.

EXPERTLY MANUFACTURED

The quality of the Palace product range is ensured by state-of-the-art manufacturing systems, which offer the required high-volume capacity to deliver Quality products every time.



EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

📍 Speke Hall Industrial Estate, Speke, Liverpool, L24 1YA

☎ +44 (0) 151 336 9104 @ sales@palacechemicals.co.uk

🌐 www.palacechemicals.co.uk

Registered No. 1377241 England

Page 2 of 2