



69-57 - GROUT FILM REMOVER



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 69-57 - GROUT FILM REMOVER

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Cleaner

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Palace Chemicals Ltd
Speke Hall Industrial Estate
L24 1YA Liverpool - United Kingdom

1.4 Emergency telephone number: 0151 486 6101

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1: Skin corrosion, Category 1, H314

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Skin Corr. 1: H314 - Causes severe skin burns and eye damage.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/protective footwear.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality.

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Substances that contribute to the classification

Urea hydrochloride

UFI: DX50-T09K-H006-19CJ

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Non-applicable

3.2 Mixture:

Chemical description: Aqueous solution based on polymers, surfactants, colourants, perfumes and additives.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 506-89-8 EC: 208-059-6 Index: Non-applicable REACH: Non-applicable	Urea hydrochloride⁽¹⁾ Self-classified	10 - <25 %
	Regulation 1272/2008 Acute Tox. 4: H302; Skin Corr. 1B: H314 - Danger	
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether⁽²⁾ Not classified	10 - <25 %
	Regulation 1272/2008	
CAS: 9004-82-4 EC: Non-applicable Index: Non-applicable REACH: Non-applicable	Sodium lauryl ether sulfate⁽¹⁾ Self-classified	1 - <2.5 %
	Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	
CAS: 2634-33-5 EC: 220-120-9 Index: 613-088-00-6 REACH: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one⁽¹⁾ ATP CLP00	<1 %
	Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	
CAS: 2682-20-4 EC: 220-239-6 Index: 613-326-00-9 REACH: 01-2120764690-50-XXXX	2-methylisothiazol-3(2H)-one⁽¹⁾ ATP ATP13	<1 %
	Regulation 1272/2008 Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317; EUH071 - Danger	
CAS: 55965-84-9 EC: Non-applicable Index: 613-167-00-5 REACH: Non-applicable	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)⁽¹⁾ ATP ATP13	<1 %
	Regulation 1272/2008 Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
	Acute	Chronic
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	10	1
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	100	100

Identification	Specific concentration limit
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	% (w/w) >=0.05: Skin Sens. 1 - H317
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	% (w/w) >=0.0015: Skin Sens. 1A - H317
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	% (w/w) >=0.6: Skin Corr. 1C - H314 0.06<= % (w/w) <0.6: Skin Irrit. 2 - H315 % (w/w) >=0.6: Eye Dam. 1 - H318 0.06<= % (w/w) <0.6: Eye Irrit. 2 - H319 % (w/w) >=0.0015: Skin Sens. 1A - H317

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 4: FIRST AID MEASURES (continued)

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

2021 Code of Practice for the Chemical Agents Regulations:

Identification	Occupational exposure limits		
	OEL (8h)	50 ppm	308 mg/m ³
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	OEL (15 min)		

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.966 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	6.81 mg/m ³	Non-applicable
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0.043 mg/m ³	Non-applicable	0.021 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	37.2 mg/m ³	Non-applicable
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.345 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1.2 mg/m ³	Non-applicable
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	Oral	0.053 mg/kg	Non-applicable	0.027 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0.043 mg/m ³	Non-applicable	0.021 mg/m ³

PNEC:

Identification				
		Systemic	Local	Systemic
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L
	Soil	2.74 mg/kg	Marine water	1.9 mg/L
	Intermittent	190 mg/L	Sediment (Fresh water)	70.2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7.02 mg/kg
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	STP	1.03 mg/L	Fresh water	0.00403 mg/L
	Soil	3 mg/kg	Marine water	0.000403 mg/L
	Intermittent	0.0011 mg/L	Sediment (Fresh water)	0.0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.00499 mg/kg
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	STP	0.23 mg/L	Fresh water	0.00339 mg/L
	Soil	0.047 mg/kg	Marine water	0.00339 mg/L
	Intermittent	0.00339 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



- CONTINUED ON NEXT PAGE -





69-57 - GROUT FILM REMOVER





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	10 % weight
V.O.C. density at 20 °C:	106.29 kg/m ³ (106.29 g/L)
Average carbon number:	7
Average molecular weight:	148.2 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Color:	Colourless
Odor:	Harsh
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	106 °C
Vapour pressure at 20 °C:	2311 Pa
Vapour pressure at 50 °C:	12177.66 Pa (12.18 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1062.8 kg/m ³
-------------------	--------------------------

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Relative density at 20 °C:	1.063
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	<2
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	75 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	270 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Not applicable	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Value	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	9510 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Urea hydrochloride CAS: 506-89-8 EC: 208-059-6	LD50 oral	500 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	LD50 oral	500 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	LD50 oral	120 mg/kg	Rat
	LD50 dermal	242 mg/kg	Rat
	LC50 inhalation	Non-applicable	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	LD50 oral	64 mg/kg	Rat
	LD50 dermal	87.12 mg/kg	Rabbit
	LC50 inhalation	0.33 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	Route	Value		
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Sodium lauryl ether sulfate CAS: 9004-82-4 EC: Non-applicable	LC50	Non-applicable		
	EC50	3.12 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	Non-applicable		
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	LC50	4.77 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	0.934 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
	Route	Value		
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	NOEC	Non-applicable		
	NOEC	0.5 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
	NOEC	4.93 mg/L		
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	NOEC	0.044 mg/L	Oncorhynchus mykiss	Fish
			Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	COD	0 g O2/g	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	73 %
	BOD5	Non-applicable	Concentration	100 mg/L
Sodium lauryl ether sulfate CAS: 9004-82-4 EC: Non-applicable	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	58.6 %
	BOD5	Non-applicable	Concentration	100 mg/L
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
	BOD5	Non-applicable	Concentration	10 mg/L
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	55.8 %
	BOD5	Non-applicable	Concentration	10 mg/L

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	BCF	1
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Pow Log	-0.06
	Potential	Low
	BCF	10
Sodium lauryl ether sulfate CAS: 9004-82-4 EC: Non-applicable	Pow Log	1.62
	Potential	Low
	BCF	2
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	Pow Log	1.45
	Potential	Low
	BCF	
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	Pow Log	-0.49
	Potential	
	Potential	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Non-applicable	Henry	OE+0 Pa·m ³ /mol
2-methylisothiazol-3(2H)-one CAS: 2682-20-4 EC: 220-239-6	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 29*	detergents containing hazardous substances	Dangerous

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste (Regulation (EU) No 1357/2014):

HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- | | |
|--|---|
| 14.1 UN number or ID number: | UN1760 |
| 14.2 UN proper shipping name: | CORROSIVE LIQUID, N.O.S. (Urea hydrochloride) |
| 14.3 Transport hazard class(es): | 8 |
| Labels: | 8 |
| 14.4 Packing group: | II |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 274 |
| Tunnel restriction code: | E |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| 14.7 Maritime transport in bulk according to IMO instruments: | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- | | |
|--|---|
| 14.1 UN number or ID number: | UN1760 |
| 14.2 UN proper shipping name: | CORROSIVE LIQUID, N.O.S. (Urea hydrochloride) |
| 14.3 Transport hazard class(es): | 8 |
| Labels: | 8 |
| 14.4 Packing group: | II |
| 14.5 Marine pollutant: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 274 |
| EmS Codes: | F-A, S-B |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| Segregation group: | SGG1 |
| 14.7 Maritime transport in bulk according to IMO instruments: | Non-applicable |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1760
14.2 UN proper shipping name: CORROSIVE LIQUID, N.O.S. (Urea hydrochloride)
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2-benzisothiazol-3(2H)-one, bronopol (INN), Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13) ; 2-methylisothiazol-3(2H)-one (Product-type 6, 11, 12, 13) ; Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13) ; bronopol (INN) (Product-type 2, 6, 11, 12, 22)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradability criteria stipulated in Regulation (EC) n°648/2004 on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

Labelling for contents:

Component	Concentration interval
Anionic surfactants	% (w/w) < 5

Preservation agents: 1,2-benzisothiazol-3(2H)-one (BENZISOTHIAZOLINONE), 2-methylisothiazol-3(2H)-one (METHYLISOTHIAZOLINONE), bronopol (INN) (2-BROMO-2-NITROPROPANE-1,3-DIOL), Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (METHYLCHLOROISOTHIAZOLINONE / METHYLISOTHIAZOLINONE).

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 15: REGULATORY INFORMATION (continued)

Chemicals (Amendment) Act 2010 (No. 32 of 2010) as amended by S.I. No. 623/2015- Safety, Health and Welfare at Work (Chemical Agents) (Amendment) Regulations 2015
Chemicals Act 2008 (No. 13 of 2008)
Safety, Health and Welfare (chemical agents) (amendment) regulations 2021 (S.I. No. 232 of 2021) and associated Code of Practice
Chemical Agents Regulations (S.I. No. 619 of 2001)
European Communities (Waste Directive) Regulations, S.I. No. 126 of 2011
S.I. No. 315/2016 - European Union (Waste Directive) (Amendment) Regulations 2016.
S.I. No. 323/2020 - European Union (Waste Directive) Regulations 2020
Chemicals Act (Control of Major Accident Hazards involving Dangerous Substances) Regulations 2015 (S.I. No. 209 of 2015)
The Chemicals Act (CLP Regulation) Regulations 2011 (S.I. No. 102 of 2011)
- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products
- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII
- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Classification procedure:

Skin Corr. 1: Calculation method

Eye Dam. 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



69-57 - GROUT FILM REMOVER



SECTION 16: OTHER INFORMATION ** (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

PALACE CHEMICALS Ltd

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -