



FENCEGUARD



ISSUE: 69-8 / 0809

**WATER-BASED
BRUSH APPLIED**

**UV RESISTANT AND
PERMANENT COLOUR**

**WATER REPELLENT
TIMBER PROTECTION**

Description:

PALACE FENCEGUARD is a water-based, low odour timber treatment specially formulated to provide attractive, long lasting outdoor protection for rough sawn timber. The water repellent, UV resistant finish is perfect for shielding fencing and garden sheds, or any other outdoor rough sawn garden construction from the ravages of rain and bright sunlight. FENCEGUARD is available in 5 colours including AUTUMN GOLD; CEDAR RED; MIDNIGHT BLUE; FIR GREEN and CHESTNUT BROWN offering the discerning gardener the range of shades to suit all seasons and selections of garden design. FENCEGUARD is safe to use in and around garden plants and foliage and it's water-based properties make splashes easy to clean from surrounding areas not intended for treatment. FENCEGUARD is supplied in 4 litre; 5 litre and 9 litre re-usable easy-seal buckets to allow direct application by brush straight to the timber.

Preparation:

Ensure all timbers are structurally sound, dry and free from loose surface coatings or growths of moss, lichen and algae (external). For timbers heavily coated with algae growth and moulds, a pre-treatment of ABICIDE FUNGICIDAL WASH is recommended prior to applying FENCEGUARD, as this will eradicate the possibility of further growth damaging the subsequently applied coating. All fabrication work, i.e. planing, sawing & boring should be completed prior to treatment and any timbers in direct contact with the ground, or affected by post treatment cutting should receive an application of a conventional wood preserver prior to treatment with FENCEGUARD.

Application:

Timbers recently saturated by rainfall, or when there is the likelihood of imminent rainfall (within 24 hours of application) are conditions to avoid if the coating is to have the chance to dry to its optimum appearance and protective capability. Also temperatures below 10°C are not conducive to rapid drying and should be avoided. FENCEGUARD is not intended for application to Decking timbers, garden furniture, hardwoods or smooth-planed structures. Timber previously coated with an oil-based treatment such as Creosote should be well weathered before the wood will be sufficiently porous to receive the FENCEGUARD treatment. Children and pets should also be kept away from treated timbers until they are completely dry and free of any traces of product.

Coverage:

Depending upon the texture and porosity of the timber to be treated, PALACE FENCEGUARD when applied as a single coat will cover at the rate of 1 litre per 4 to 6 square metres, either by brush or spray application method. In warm summer conditions, allow 2 to 6 hours drying time. When applying a second coat always make sure the first is dry and allow for a longer drying period. Clean equipment immediately with warm, soapy water and rinse thoroughly.

NOTE: The colour label on the container indicates approximate colour only.

Precautions:

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of soap and water or a recognised skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice. May be Harmful if swallowed. Keep out of reach of children; Keep away from food, drink and animal feeding stuffs.

Storage & Packaging:

FENCEGUARD is available in 4; 5 & 9 litre polypropylene containers. Store in cool, well-ventilated conditions away from direct sources of heat. When transporting the container always ensure it is secured in a stable upright position and retained to prevent movement during carriage. Should further more specific technical information be required, contact the Palace Technical helpline on 0151 486 6101.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

EN ISO 9001



FM 01010



PALACE CHEMICALS Ltd

Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB
Tel: 0151 486 6101 – Fax: 0151 448 1982 e-mail:
sales@palacechemicals.co.uk

LANGLOW



EN ISO 14001



EMS 85788