



TILE AFTERCARE GROUT FILM REMOVER



Issue 1 – ACGFR / 0809

**CONCENTRATED
ACID BASED CLEANER**

**REMOVES CEMENT-FILM
AND EFFLORESCENCE**

**SUITABLE FOR USE ONLY ON ACID
RESISTANT CERAMIC SURFACES**

DESCRIPTION:

Palace Grout Film Remover will soften and remove the excess cement film from the tiled surface which is often left after the grout has been applied, but will not affect the grout remaining within the tile joints. Grout Film Remover will also remove lime scale and surface efflorescence which sometimes forms on the surface of the grout joint in the first few weeks after application.

APPLICATION:

To ensure the tiled surface is not acid sensitive, test-apply a few drops to a small innocuous area. If no reaction or permanent surface discoloration is observed then Dilute Grout Film Remover as 1 part to up to 7 parts with water and spread this solution evenly across a pre-wet surface. Apply the solution liberally and spread over the surface, covering no more than 10 - 15 m² at a time, applying mild abrasion to areas where hardened cement film has accumulated. Grout Film Remover should only be used neat where heavy cement deposits have built up. Allow the solution to remain for about 10 minutes then flush the surface clean 2 or 3 times with copious volumes of clean water and scrub thoroughly with a synthetic fibre abrasive pad or a stiff brush and mop up. Rinse well with water at least 2 - 3 times. If necessary and repeat the application locally where any residual stains remain.

COVERAGE:

When diluted, this product will cover up to 10 square metres per litre, depending on surface texture and the degree of staining to be removed. **Warning: Grout Film Remover should not be used on Calcareous Natural Stone, Travertine, Marble, slate, terrazzo, Granito, Cementitious tiles and any other acid sensitive surfaces.**

PROPERTIES:

Grout Film Remover is designed for use on any non-calcareous tiled surfaces which are resistant to acid attack. This product is a blend of non-ionic surfactants, inorganic acids and sequestering agents designed to lift cement-based film, lime-scale and efflorescent residues from the surface and leave a clean bare tiled surface finish which may then be further treated with an appropriately selected surface protective sealer.

HEALTH & SAFETY PRECAUTIONS:

May be corrosive to metals. Harmful if swallowed.

Causes skin irritation. Causes serious eye damage

Keep locked up and out of the reach of children. Avoid contact with skin & eyes.

In case of contact with eyes rinse immediately with water and seek medical attention.

Remove and launder all contaminated clothing. Do not empty directly into drains or watercourses.

Wear suitable gloves, eye/face protection, PVC overalls and rubber boots when in use.

If swallowed seek medical advice immediately and show this label.



DANGER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

EN ISO 9001



FM 01010



PALACE CHEMICALS Ltd

Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB

Tel: 0151 486 6101 – Fax: 0151 448 1982

e-mail: sales@palacechemicals.co.uk



EN ISO 14001



EMS 85788