



# SUPER VALUE MATT



Issue date: 43-17 / 0809

**APPLY BY BRUSH  
OR ROLLER**

**AVAILABLE IN  
WHITE & MAGNOLIA**

**ECONOMICAL &  
INSTANT COVERAGE**

## DESCRIPTION:

PALACE SUPER VALUE MATT is a high opacity decorative water-borne matt emulsion for interior use on wall and ceiling surfaces, which can be applied over most types of existing paint or onto suitably primed and prepared sound wall & ceiling surfaces. PALACE SUPER VALUE MATT can be applied by brush or roller to give highly economical quick-drying hiding power and coverage over most surface types and dries out to a bright, clean matt finish refreshing the surface appearance.

## SURFACE PREPARATION:

Surfaces to be treated should be sound, clean, dry and free from loose flaking materials, oil and grease stains. Surface defects and cracks should be repaired with a suitable repair mix; filler or sealant. Scrape back to a firm edge all areas of existing loose flaking coatings and rub down thoroughly to 'key and feather' exposed edges of the original painted surface if applicable. Repair cracks or damaged areas with PALACE POWDER FILLER and allow it to dry before sanding to a smooth level and even finish. New surfaces can be primed with a thinned coat of PALACE PVA diluted with 1 part to 4 parts added water. Old, worn or very porous & friable surfaces should be sealed with a coat of PALACE MASONRY STABILISING SOLUTION before painting can proceed.

## APPLICATION METHOD:

Stir well before use. PALACE SUPER VALUE MATT can be applied either by a generously loaded brush or roller to achieve the best results. Two coats will normally be sufficient to give a satisfactory finish depending on the condition of the base substrate however on darker, patchy surfaces three coats may be needed for complete coverage. Allow up to 6 hours between coats for drying under normal, well ventilated ambient conditions. Work down from the top of the elevation, keeping the sections painted small enough to ensure that the edges to be joined are still wet as work progresses.

## COVERAGE:

5 litres of PALACE SUPER VALUE MATT will cover up to 30 square metres as a two-coat application over a smooth even surface, depending upon the condition, texture and porosity of the surface being coated. Care should be taken to ensure all windows and surfaces not intended for coverage are covered and well protected during the application of this product. Brushes and rollers can be readily cleaned immediately after use with warm soapy water. Splashes on skin should be cleaned off immediately with warm soapy water and not allowed to dry out unattended. Wear suitable protective clothing at all times during application, including boots, overalls, goggles and head protection.

## HEALTH & SAFETY:

Ensure good ventilation during application and drying. Avoid contact with skin and eyes.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Wear eye protection during paint application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser.

Keep out of the reach of children. Do not use or store by hanging on a hook.

**VOC Directive:** EU Limit value for this product (Cat A/c): 150 g/l (2007)/ 100g/l (2010). This product contains max 15 g/l VOC

## STORAGE & PACKAGING:

Store in a secure upright and sealed condition during transit and when in storage and protect from frost or temperatures less than 5°C or in excess of 35°C. Minimum shelf-life is 1 year from date of manufacture. PALACE SUPER VALUE MATT is available in re-sealable 5 litre and 10 litre buckets. Should further more specific technical information be required, contact the Palace Technical helpline on 0151 486 6101.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

EN ISO 9001



FM 01010



**PALACE CHEMICALS Ltd**

Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB  
Tel: 0151 486 6101 – Fax: 0151 448 1982 e-mail:  
sales@palacechemicals.co.uk

**LANGLOW**



EN ISO 14001



EMS 85788