



TEXTURED PAINT



Issue date: 43-20 / 0809

BRILLIANT WHITE TEXTURED COATING

HIGH-BUILD COARSE FINISH

SEALS OVER CRACKS & UNEVEN SURFACES

DESCRIPTION:

PALACE TEXTURED PAINT is a durable acrylic-based interior / exterior protective coating, designed specifically for use over most sound porous & semi-porous surfaces to give a coarse textured, rough surface finish which covers any cracks and imperfections on the receiving substrate. PALACE TEXTURED PAINT can be applied by brush or roller to give excellent coverage and it's highly viscous formula enables it to be applied with textured sweeps, ridges & patterns to enhance the textured profile of the final finish.

SURFACE PREPARATION:

Surfaces to be treated should be sound, clean, dry and free from loose flaking materials, oil and grease stains. Any surface mould or fungal growths should be pre-treated with ABICIDE FUNGICIDAL WASH to remove surface mould or lichen growth. Surface defects and cracks should be repaired with a suitable repair mix; filler or sealant. Scrape back to a firm edge all areas of existing loose flaking coatings and rub down thoroughly to 'key and feather' exposed edges of the original painted surface if applicable. Repair cracks or damaged areas with PALACE INTERIOR POWDER FILLER or on external walls use a QUICK SET PATCHING CEMENT and allow it to dry. Old, worn or very porous & friable surfaces should be sealed with a coat of PALACE MASONRY STABILISING SOLUTION before painting can proceed..

APPLICATION METHOD:

Stir well before use. PALACE TEXTURED PAINT can be applied either by a generously loaded brush, roller or a texturing tool to achieve the best results. Two coats will normally be sufficient to give a satisfactory finish depending on the condition of the base substrate. Allow up to 6 hours between coats for drying under normal, well ventilated ambient conditions. Work down from the top of the elevation, keeping the sections painted small enough to ensure that the edges to be joined are still wet as work progresses. Do not apply in temperatures below 5°C or when rainfall is likely within a day of being painted.

COVERAGE:

5 litres of PALACE TEXTURED PAINT will cover about 20 square metres when applied as two consecutive coats depending upon the condition, texture and porosity of the surface being coated. Care should be taken to ensure all windows and surfaces not intended for coverage are covered and well protected during the application of this product. Brushes and rollers can be readily cleaned immediately after use with warm soapy water. Splashes on skin should be cleaned off immediately with warm soapy water and not allowed to dry out unattended. Wear suitable protective clothing at all times during application, including boots, overalls, goggles and head protection.

HEALTH & SAFETY:

Ensure good ventilation during application and drying. Avoid contact with skin and eyes.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Wear eye protection during paint application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser.

Keep out of the reach of children. Do not use or store by hanging on a hook.

VOC Directive: EU Limit value for this product (Cat A/c): 150 g/l (2007)/ 100g/l (2010). This product contains max 23 g/l VOC

STORAGE & PACKAGING:

Store in a secure upright and sealed condition during transit and when in storage and protect from frost or temperatures less than 5°C or in excess of 35°C. Minimum shelf-life is 1 year from date of manufacture. PALACE TEXTURED PAINT is available only in 5 litre buckets. Should further more specific technical information be required, contact the Palace Technical helpline on 0151 486 6101.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

EN ISO 9001



FM 01010



PALACE CHEMICALS Ltd

Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB
Tel: 0151 486 6101 – Fax: 0151 448 1982 e-mail:
sales@palacechemicals.co.uk

LANGLOW 



EN ISO 14001



EMS 85788