



TILE AFTERCARE PORCELAIN SEALER



Issue 1 – ACPS – 3/2015

**FOR USE ON POLISHED
AND IMPERMEABLE SURFACES**

**PROTECTS AND ENHANCES
POLISHED PORCELAIN & STONE**

**BUFFS UP TO A
SPARKLING FINISH**

DESCRIPTION:

Porcelain Sealer is a clear ready to use spirit based liquid designed for sealing and protecting dense and impermeable surfaces such as porcelain, vitrified and granite tiles with dense impermeable surfaces which have been prepared to a polished shiny finish. The application of a very thin layer of Porcelain Sealer will inhibit staining and maintain the original “as new” look of the tiled surface when the tiles are polished and re-buffed after the treatment has dried.

APPLICATION:

Newly laid tiles need at least 7 days to dry and must be completely clean and well buffed to a polished finish before Porcelain Sealer can be applied. Remove all existing stains and previous sealers using a suitably selected cleaning agent then allow the tiles to dry for 24 hours. NB. Always pre-test a small area to ensure no colour change occurs. Apply neat using a fine flat brush; velvet fibre-free cloth or fine sponge to achieve a single fine thin and continuous even coat then leave for about 24 hours. Once the treatment has been allowed to dry on the tiles, mechanically buff the surface vigorously and evenly with a single disc felt pad professional cleaner to return and enhance the final polished shiny appearance of the porcelain. It is essential to ensure the buffing and re-polishing is evenly and thoroughly applied across all areas to ensure the tile returns to its' optimum shiny appearance.

COVERAGE:

Depending on surface texture and porosity, one litre of ready to use Porcelain Sealer will be sufficient to protect between 20 - 40 square metres of a smooth porous surface for a single coat application. Repeat coats may be needed depending on the type of tile and the level of foot traffic the area is subject to. To ensure the optimum surface appearance is achieved ensure buffing is vigorously applied over the full treated area with a smooth felt pad using a mechanical applicator.

PROPERTIES:

Palace Porcelain Sealer is a spirit based surface protective treatment ideal for application onto porcelain, granite and polished vitrified tiles where protection is required from stains which may be caused by surface liquid absorption of oil, grease or water based liquids.

HEALTH & SAFETY PRECAUTIONS:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes damage to organs Central nervous system through prolonged or repeated exposure if inhaled. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do NOT induce vomiting. IF SWALLOWED: Immediately call a doctor / NHS Direct. IF ON SKIN: Wash with plenty of soap and water. Do not breathe vapours. IF INHALED: Remove victim to fresh air and keep in a position comfortable for breathing. Do not get in eyes, on skin, or on clothing. IF ON SKIN Remove immediately all contaminated clothing. Rinse skin with water/shower. Store in a well-ventilated place. Keep container tightly closed Keep cool.



DANGER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.

EN ISO 9001



FM 01010



PALACE CHEMICALS Ltd

Speke Hall Industrial Estate; Speke; Liverpool; L24 4AB

Tel: 0151 486 6101 – Fax: 0151 448 1982

e-mail: sales@palacechemicals.co.uk



EN ISO 14001



EMS 85788