



# TILERS PRIMER - SBR



ISSUE DATE: TP – 2 / 0319

**BONDING AGENT FOR  
DIFFICULT SURFACES**

**WATER RESISTANT  
SURFACE SEALER**

**PRIMER FOR  
POROUS SUBSTRATES**

## Description:

**PALACE TILERS PRIMER** is a styrene butadiene co-polymer emulsion for use as a primer; bonding agent and sealer formulated to improve, adhesion strength and long-term durability of the bond between the adhesive and any surface substrate. It is a safe to use and can be applied to a wide range of building materials including applications where contact with water is likely. **PALACE TILERS PRIMER** can be used as a water-proof bonding agent when mixed as a slurry with neat cement and can readily be incorporated into mixes of sand cement screeds, plasters and renders, giving a water reducing and plasticising effect, as well as improving wet-tack and adhesion of the render to the existing base masonry. **PALACE TILERS PRIMER** is an excellent primer for porous surfaces such as gypsum plaster, old / worn concrete; sand cement screeds and render by reducing porosity, surface dusting and improving initial tack so that subsequently applied adhesives, renders or screeds can achieve a secure and lasting key with the base substrate.

## TILERS PRIMER as a PRIMING COAT:

Once porous, worn or dusty concrete floors have been thoroughly cleaned of all dust, oil & loose surface matter, **PALACE TILERS PRIMER** diluted as 1 part to 3 parts with water and brushed on as a generous single coat, can seal the surface, reduce suction and inhibit further dusting. One coat is normally sufficient for priming surfaces ready to receive an application of **PALACE SELF-LEVELLING COMPOUND** or any **PALACE TILE ADHESIVE**, however very porous surfaces may require two coats or use a 1:1 dilution to effectively reduce porosity and bind the surface. Cracked or friable surfaces should be repaired before laying any top coatings. **PALACE TILERS PRIMER** is effective on gypsum plaster, porous cement render walls, worn concrete, cement sand floor screeds, cement panel-boards and timbers such as chipboards and worn plywood. Plaster walls which have been over-finished to a polished appearance should be slightly roughened with a stiff brush and wiped clear of loose fines before priming.

## TILERS PRIMER as a SEALER:

Timber and composite panels should be clean and free from dust and loose flaking material before being sealed on all exposed faces and edges with neat **PALACE TILERS PRIMER**, then the 1 to 3 parts water dilution brushed across the surface to be tiled. Adhesive may be applied to the primed surface whilst it is still slightly tacky to touch. Gypsum based materials likely to be tiled over with a cement-based adhesive, such as Anhydrite floor screeds or Gypsum finishing plasters must be effectively sealed with 2 coats of neat **PALACE TILERS PRIMER** the first as a 1 to 1 part water dilution and the second applied neat with each being allowed to dry before proceeding with the next application.

## Application as a BONDING AGENT:

**PALACE TILERS PRIMER** can be used as a bonding agent when over-laying existing masonry with a fresh coat of render, plaster, concrete or screed, or when applying cement-based tile adhesives to difficult, non-porous surfaces such as existing vinyl floor tiles and steel decking. Wet down the exposed surface so that it is damp but not holding standing water. **PALACE TILERS PRIMER** can be mixed to a brushable slurry consistency using a mechanical agitator by adding approximately 1-part **PRIMER** to 1 part neat cement (or 1 part cement based adhesive) to be spread out using a stiff brush, evenly and consistently over the surface. Application of the topping screed or adhesive should proceed before the bonding slurry has completely dried out as surface tackiness will improve the adhesive key. **PALACE TILERS PRIMER** bonding slurry can also be used as a waterproof tanking slurry when applied as a three-coat treatment to prepared masonry.

## TILERS PRIMER as a CEMENT SCREED / MORTAR ADMIXTURE:

When repairing concrete floors, steps or applying vertical renders, **PALACE TILERS PRIMER** should be mixed at the minimum rate of 5 litres per 50 kg of Ordinary Portland Cement, or adding up to 15 litres where heavy traffic or loads are expected. Mix designs for repair mortars are ideally 1 part OPC to 3 parts zone 3 washed dried sand. When laying thick-section screeds (25 to 50mm) replace 1 part sand with 1 part 6mm dried coarse aggregate and always add just sufficient water to give the mix the required consistency for ease of application. **PALACE TILERS PRIMER** imparts a strong water-reducing and plasticising effect in concrete and mortar, thus giving improved strength, shrink resistance, long term durability, abrasion resistance and reduced water permeability.

## Coverage:

The consumption of **PALACE TILERS PRIMER** for any particular application depends heavily upon the texture and porosity of the surface it is applied to and the figures shown below are intended as a rough guide only:

APPLICATION:	COVERAGE:
ADMIXTURE:	5 to 15 litres per 50kg of OPC.
BONDING SLURRY:	3 - 5 square metres per litre.
PRIMER / SEALER:	Up to 20 square metres per litre.

## Storage & Packaging:

**PALACE TILERS PRIMER** is supplied either as a 5 litre or 1 litre bottle and has a storage life of not less than 12 months if stored in dry, un-opened conditions. Consult the **PALACE TILERS PRIMER** material safety data sheet for advice on handling and safety procedures.

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. However it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.



Palace Chemicals Ltd.  
Speke Hall Industrial Estate, Speke, Liverpool L24 1 YA  
Tel: 0151 486 6101 Fax: 0151 448 1982  
Email: sales@palacechemicals.co.uk

