

DECLARATION OF PERFORMANCE

No. 83-16/ 1-CPR-2025

1. Unique identification code of the product type:
PALACE AQUABAN / SHOWER-TIGHT LIQUID WATERPROOF TANKING MEMBRANE
2. Batch / serial No. identifying the construction product as required under Article 11(4)
NB. Batch number is printed on the side of the inner bucket with date of manufacture.
3. Intended use in accordance with the harmonised standard:
Liquid waterproof membrane for use beneath tile and stone
4. Name & contact address of the Manufacturer:
**PALACE CHEMICALS Ltd
Speke Hall Industrial Estate; Speke; Liverpool
L24 1YA**
5. Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)
Not applicable
6. System of assessment & verification of constancy of performance as set out in Annex V:
System 2+
7. Harmonised EN Standard:
EAD 030352-00-0503
**The Notified Body Lucideon (Previously Named Ceram) NB 1289 performed the Initial Type Testing under attestation system 2+ and issued the following report:
Test report – code to be confirmed**
8. Declared Performance:
To harmonised technical specification: EAD 030352-00-0503

Essential characteristics	Performance	Harmonised technical specification
Watertightness: Crack bridging ability Bond Strength to concrete: Bond Strength to gypsum board Scratch Resistance: Joint bridging ability – EAD030352-00-0503-2.2.8 Water Vapour permeability (EN/ISO 12572): 2 X 500 gm/M2 - AQUABAN Thickness – EAD 030352-00-0503:2019 Annex D Watertightness around penetrations: - Annex A (Floor) - Annex F (Wall) Resistance to temperature, (i) Adhesion Resistance to temperature, (ii) Crack bridging ability Resistance to water Resistance to Alkalinity Resistance to Climate / Heat ageing – Tensile adhesion Resistance to freeze thaw cycles Repairability (Strength after repair) EAD 030352-00-0503 Reaction to Fire Release of dangerous substances	Pass Pass as category 1 Pass (≥ 0.5 MPa) Pass (> 0.5 MPa) NPD Pass as category 2 Sd = 33.6m TBA 0.4mm = 3.5kg / (mmx m2) 0.5mm = 2.3kg / (mmx m2) 0.6mm = 2.6kg / (mmx m2) Pass as category 2 Pass as category 2 Pass (≥ 0.5 MPa) Pass (≥ 0.75 mm) Pass (≥ 0.5 MPa) Pass (≥ 0.5 MPa) Pass (≥ 0.5 MPa) Pass (≥ 0.5 MPa) Repairable NPD See MSDS	EAD 030352-00-0503

9. Declaration:

The performance of the product identified in above is in conformity with the declared performance as defined under EAD 030352-00-0503. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for & behalf of



Jim Percival - Technical Director – Palace Chemicals Ltd

Palace Chemicals Ltd:

Date: 21st June 2025