



**No. 0335-0050-21/ 1-CPR/2013**  
**DECLARATION OF PERFORMANCE**

1. Unique identification code of the product type:  
**LATICRETE 335 SUPERFLEX GREY**
2. Batch / serial No. identifying the construction product as required under Article 11(4)  
**NB. Batch number is printed on the side of the bag with date of manufacture.**
3. Intended use in accordance with the harmonised standard:  
**Improved cementitious deformable adhesive with extended open time & reduced slip for internal & external tiling**
4. Name & contact address of the Manufacturer:  
**Laticrete UK Ltd**  
**Speke Hall Industrial Estate; Speke; Liverpool**  
**L24 1YA**
5. Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)  
**Not applicable**
6. System of assessment & verification of constancy of performance as set out in Annex V:  
**System 3**
7. Harmonised EN Standard:  
**EN 12004:2007 + A1:2012**  
**The notified body No. NB1289 CERAM (LUCIDEON) performed the test according to EN 12004:2007 + A1:2012**  
**under system 3 and issued the following report:**  
**Test report (111087)-4949**
8. Declared Performance:  
**To harmonised technical specification: EN 12004:2007 + A1:2012**

Essential characteristics	Performance	Harmonised technical specification
<b>Bond strength as:</b> <ul style="list-style-type: none"> <li>• Initial Tensile adhesion strength</li> </ul> <b>Open time tensile adhesion strength:</b> <ul style="list-style-type: none"> <li>• Tensile strength after 30 minutes open time</li> </ul> <b>Durability for:</b> <ul style="list-style-type: none"> <li>• Tensile adhesion strength after heat ageing</li> <li>• Tensile adhesion strength after freeze thaw cycles</li> <li>• Tensile adhesion strength after water immersion</li> </ul> <b>Reaction to Fire</b> <b>Reduced Slip</b>	> 1.0 N/mm <sup>2</sup> > 0.5 N/mm <sup>2</sup> > 1.0 N/mm <sup>2</sup> > 1.0 N/mm <sup>2</sup> > 1.0 N/mm <sup>2</sup> Class F < 0.5mm	<b>EN 12004:2007 +            A1:2012</b>
<b>Release of dangerous substances</b>	See MSDS	

9. Declaration:  
**The performance of the above product identified in points 1 & 2 is in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued under the sole responsibility of The manufacturer identified in point 4**

Signed for & behalf of  
 Laticrete Ltd:

Jim Percival - Technical Director – Laticrete UK Ltd

Date: 24<sup>th</sup> March 2014



**LATICRETE UK Ltd**  
 Speke Hall Industrial Estate;  
 Speke; Liverpool; L24 4AB  
 Tel: 0151 486 6101 – Fax: 0151 448 1982  
 e-mail: jp@laticrete.co.uk

