


Ver 03 - PALBAO 25.08.21

BORDER & OVERLAP

READY MIXED ADHESIVE FOR VINYL & PAPER BORDER ROLLS

- EASY TO APPLY
- BONDS TO ALREADY PAPERED SURFACES
- IDEAL FOR HEAVY DUTY PAPERS
- DUAL REPAIRING FUNCTION
- CONTAINS A PROTECTIVE BIOCID



LANGLOW BORDER & OVERLAP

Is a ready mixed, high-strength adhesive, suitable for hanging vinyl and paper border rolls. Allows for repairs to existing wall coverings, especially situations where vinyl to vinyl contact is present. You can also use Border & Overlap for over-lapping seams, where higher strengths are required.

EXCELLENT
GRAB

FIXES TO ALL TYPE OF
WALL COVERINGS

BORDER & OVERLAP

Ready Mixed Adhesive for Vinyl & Paper Border Rolls



DESCRIPTION

LANGLOW BORDER & OVERLAP is formulated for hanging rolled borders to most types of surface including existing decorative coatings and ensuring good adhesion is achieved when over-lapping wall-coverings need to be fixed including blown vinyl; heavy duty textile wall-coverings and polystyrene. The product is intended for application by brush or roller, ensuring a liberal covering is achieved up to and including all the edges and corners. Apply a faint pencil or chalk line on the surface to establish the horizontal level and then carefully apply the coated border up to the guide line. Smooth into position and remove any excess adhesive at once with a clean damp cloth. This product contains a fungicidal preservative.

SURFACE PREPARATION

Ensure the receiving surface is thoroughly clean dry and free of any grease or deleterious material, such as dust and loose flaking old surface coatings. Check to see that any adjoining frames or structures are firmly braced and free from movement. Cover and seal any nail heads or screw fixings with an oil-based gloss paint to ensure a level and even surface.

APPLICATION METHOD

Apply the adhesive liberally by brush or roller and always follow the covering manufacturers' instructions which are specified for the Border roll being applied:

OVERLAPPING SEAMS can be fixed with an even spread of adhesive applied onto the contact face of the receiving wall covering with the over-lapping piece then being smoothed down firmly with a hard roller, removing any squeezed out excess adhesive with a clean damp cloth as you go along the overlap.

WALLPAPER REPAIRS can be made by first moistening the back of the vinyl or heavy wallpaper, then liberally spread the **LANGLOW BORDER & OVERLAP** adhesive onto the expose wall and press the paper firmly back in place.

STORAGE AND PACKAGING

LANGLOW BORDER & OVERLAP is supplied in 0.5kg & 1.0kg tubs and has a storage life of not less than 12 months if kept in dry, un-opened conditions away from frost or elevated temperatures (> 35°C).

HEALTH AND SAFETY

A complete PALACE material safety data sheet is available on request or online at www.palacechemicals.co.uk

QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at:

<http://www.palacechemicals.co.uk>

DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate, however it is given without guarantee, as conditions of use and workmanship involved are both beyond our control. All information supplied is subject to the company's terms and conditions of sale, copies of which are available on request.



EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

EN ISO 18001



OHS 596309

PALACE CHEMICALS LTD

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 - FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK