

## DECLARATION OF PERFORMANCE

No. 82-62 / 1-CPR/2022

1. Unique identification code of the product type:

**NX RAPID SET FLEXI WALL & FLOOR TILE ADHESIVE - GREY (82-62)**

2. Batch / serial No. identifying the construction product as required under Article 11(4)

**NB. Batch number is printed on the side of the bag with date of manufacture.**

3. Intended use in accordance with the harmonised standard:

**Improved deformable fast setting cementitious adhesive with reduced slip and extended open time for internal & external tiling**

4. Name & contact address of the Manufacturer:

**PALACE CHEMICALS Ltd**  
**Speke Hall Industrial Estate; Speke; Liverpool**  
**L24 1YA**

5. Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)

**Not applicable**

6. System of assessment & verification of constancy of performance as set out in Annex V:

**System 3**

7. Harmonised EN Standard:

**EN 12004:2007 + A1:2012**

**The notified body No. NB1289 CERAM (LUCIDEON) performed the test according to EN 12004:2007 + A1:2012 under system 3 and issued the following report:**  
**Test report (104751)-22375.**

8. Declared Performance:

**To harmonised technical specification: EN 12004:2007 + A1:2012**

Essential characteristics	Performance	Harmonised technical specification
<b>Bond strength as:</b> <ul style="list-style-type: none"> <li>Early tensile adhesion strength</li> <li>Initial Tensile adhesion strength</li> </ul> <b>Extended open time tensile adhesion strength:</b> <ul style="list-style-type: none"> <li>Tensile strength after 30 minutes open time</li> </ul> <b>Durability for:</b> <ul style="list-style-type: none"> <li>Tensile adhesion strength after heat ageing</li> <li>Tensile adhesion strength after freeze thaw cycles</li> <li>Tensile adhesion strength after water immersion</li> </ul> <b>Reaction to Fire</b> <b>Reduced Slip</b> <b>Deformability</b>	<b>&gt; 0.5 N/mm<sup>2</sup></b> <b>&gt; 1.0 N/mm<sup>2</sup></b>  <b>&gt; 0.5 N/mm<sup>2</sup></b>  <b>&gt; 1.0 N/mm<sup>2</sup></b> <b>&gt; 1.0 N/mm<sup>2</sup></b> <b>&gt; 1.0 N/mm<sup>2</sup></b> <b>Class A1</b> <b>&lt; 0.5mm</b> <b>&gt; 2.5mm</b>	<b>EN 12004:2007 + A1:2012</b>
<b>Release of dangerous substances</b>	<b>See MSDS</b>	

9. Declaration:

**The performance of the above product identified in points 1 & 2 is in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4**

Signed for & behalf of  
Palace Chemicals Ltd:



Jim Percival - Technical Director – Palace Chemicals Ltd

Date: 21<sup>st</sup> June 2021