

DECLARATION OF PERFORMANCE

No. 82-60 / 1-CPR/2021

1. Unique identification code of the product type:

NX STANDARD SET FLEXI ADHESIVE - GREY (82-60)

2. Batch / serial No. identifying the construction product as required under Article 11(4)

NB. Batch number is printed on the side of the bag with date of manufacture.

3. Intended use in accordance with the harmonised standard:

Improved Normal setting Deformable cementitious adhesive with reduced slip & extended open time for internal & external tiling

4. Name & contact address of the Manufacturer:

**PALACE CHEMICALS Ltd
Speke Hall Industrial Estate; Speke; Liverpool
L24 1YA**

5. Name & contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)

Not applicable

6. System of assessment & verification of constancy of performance as set out in Annex V:

System 3

7. Harmonised EN Standard:

EN 12004:2007 + A1:2012**The notified body No. NB1020 CERAM (LUCIDEON) performed the test according to EN 12004:2007 + A1:2012 under system 3 and issued the following report:
Test report (111087)-4949.**

8. Declared Performance:

To harmonised technical specification: EN 12004:2007 + A1:2012

Essential characteristics	Performance	Harmonised technical specification
Bond strength as: <ul style="list-style-type: none"> Initial Tensile adhesion strength Open time tensile adhesion strength: <ul style="list-style-type: none"> Tensile strength after 30 minutes open time Durability for: <ul style="list-style-type: none"> Tensile adhesion strength after heat ageing Tensile adhesion strength after freeze thaw cycles Tensile adhesion strength after water immersion Reaction to Fire Reduced Slip Deformable	> 1.0 N/mm² > 0.5 N/mm² > 1.0 N/mm² > 1.0 N/mm² > 1.0 N/mm² Class E < 0.5mm > 2.5mm	EN 12004:2007 + A1:2012
Release of dangerous substances	See MSDS	

9. Declaration:

The performance of the above product identified in points 1 & 2 is in conformity with the declared performance as defined under EN 12004:2007 + A1:2012. This declaration of performance is issued under the sole responsibility of The manufacturer identified in point 4Signed for & behalf of
Palace Chemicals Ltd:

Jim Percival - Technical Director – Palace Chemicals Ltd**Date: 21st June 2023**

EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

PALACE CHEMICALS LtdSpeke Hall Industrial Estate;
Speke; Liverpool; L24 1YA
Tel: 0151 486 6101 – Fax: 0151 448 1982
e-mail: sales@palacechemicals.co.uk**BASA**