



# TECHNICAL DATA SHEET

DEC 2025 Ver 01 - PALGHRR 01.12.25



# GROUT HAZE & RESIN REMOVER

GROUT & POLYMER RESIDUE REMOVER

- Ready to use gel-like formula
- Ideal for porcelain tiles and other non porous surfaces
- Works in less than 20 mins
- Removes resin haze & grout residue

## DESCRIPTION

**PALACE GROUT HAZE & RESIN REMOVER** is designed to remove the after-effects of haze or bloom from epoxy grout that has been left on the tiled surface along with oil, grease deposits, paint and other organic substances. This viscous, pourable liquid incorporates a blend of non-corrosive and non-flammable polar solvents, which is an ideal product to use where more harmful chemicals are restricted.

## APPLICATION

Apply the **PALACE GROUT HAZE & RESIN REMOVER** to the tiled surface using a brush or roller to a thickness of between 1-2mm and allow to work for approximately 2-3 hours before washing off with an emulsifying pad and warm water with detergent and moping / wiping dry. If the haze / coating is more stubborn, then a further application may be required, allowing longer time for the product to breakdown the substance (up to 4-5 hours) prior to washing off as directed above.

**Note:** It is always advisable to conduct a test area on a spare tile or an inconspicuous area prior to application to the full tiled area.

## TECHNICAL DATA

|                          |                       |
|--------------------------|-----------------------|
| UNIT SIZE                | 1L                    |
| CONSISTENCY              | Gel                   |
| COLOUR                   | Transparent           |
| DENSITY                  | 1.10g/cm <sup>3</sup> |
| PH                       | -                     |
| APPLICATION TEMPERATURES | 0 - 40°C              |
| WAIT TIME BEFORE RINSING | 30 Mins               |

EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

📍 Speke Hall Industrial Estate, Speke, Liverpool, L24 1YA

☎ +44 (0) 151 336 9104 @ sales@palacechemicals.co.uk

🌐 www.palacechemicals.co.uk

Registered No. 1377241 England



# TECHNICAL DATA SHEET

DEC 2025 Ver 01 - PALGHRR 01.12.25

## COVERAGE

If applied at a thickness of 2mm, 1 litre of **PALACE GROUT HAZE & RESIN REMOVER** will cover approximately 10m<sup>2</sup> depending on the texture of the tiles.

## STORAGE

Store in cool, dry, well-ventilated conditions, away from sources of heat, direct sunlight or exposure to frost. Always completely reseal the container after partial use. Keep away from Children.

## PROPERTIES

**PALACE GROUT HAZE & RESIN REMOVER** is a blend of highly polar solvents which is ideal for use where more harmful chemicals are restricted. The product is a viscous, pourable clear liquid with excellent film solvency designed to soften multiple & enable epoxy resin residues to be wiped clean in a single application.

## HEALTH & SAFETY



**WARNING**

**Causes serious eye irritation.**

**May cause an allergic skin reaction.**

Avoid breathing vapours. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/protective footwear. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

## QUALITY & ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

## TECHNICAL ADVICE

Should further technical information be required, call the Palace Chemicals Technical Helpline on 0151 336 9104.

## DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or control over where and how our products are stored and used. All products are sold and guaranteed subject to our terms and conditions of sale, copies of which may be obtained on request.

## EXTENSIVE PRODUCT RANGE

We offer the most extensive range of Tiling & Flooring products in the UK.

## EXPERTLY MANUFACTURED

The quality of the Palace product range is ensured by state-of-the-art manufacturing systems, which offer the required high-volume capacity to deliver Quality products every time.



EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

📍 Speke Hall Industrial Estate, Speke, Liverpool, L24 1YA

☎ +44 (0) 151 336 9104 @ sales@palacechemicals.co.uk

🌐 www.palacechemicals.co.uk

Registered No. 1377241 England

Page 2 of 2