

Ver 04 - PALTASS 28.10.24

TERRACOTTA & STONE SEALER

NATURAL OIL SEALER

- IDEAL FOR TRADITIONAL TERRACOTTA & QUARRY TILES
- DRIES TO A SHEEN FINISH
- NATURAL OIL BASED FORMULA
- ONE COAT CLEAR FINISH
- PROVIDES A RICH AUTHENTIC FINISH



PALACE TERRACOTTA & STONE SEALER

Is a natural oil based treatment, which has long been used as the traditional means of sealing and protecting rustic floors. Terrace and Stone Sealer can be applied to original terracotta, stone and slate to protect from the ingress of moisture, damp and stain bearing deposits.

TERRACOTTA
TILES

PROVIDES A RICH
AUTHENTIC FINISH

TERRACOTTA & STONE SEALER

Natural Oil Sealer



DESCRIPTION

PALACE TERRACOTTA & STONE SEALER is a linseed oil based treatment used to seal and protect rustic floors such as Terracotta, Stone & Slate from the ingress of moisture, damp and stain bearing deposits. This treatment may slightly darken the appearance of previously untreated, porous surfaces, but will provide a rich satin lustre, intensifying the natural colours and shades which are a unique feature of this type of traditional ceramic flooring.

APPLICATION METHOD

Ensure the surface is thoroughly clean, dry and free of all surface deposits. An application of **PALACE ALL PURPOSE TILE CLEANER** the day before may assist in achieving an ideal clean surface. Floors must be left to dry for at least 3 days and any under-floor heating switched off 24 hours prior to applying **PALACE TERRACOTTA & STONE SEALER**. Apply the product sparingly with a smooth roller or non-fibrous cloth working in one direction and allow it to soak in for about 5 – 10 minutes before wiping away any excess treatment with a cloth lightly soaked in **PALACE WHITE SPIRIT**. Highly porous surfaces may require a repeat treatment until no further uptake into the stone is observed. Drying time under ambient conditions will be about 3 to 4 hours. The final appearance should be a soft sheen finish and the surface will be open to foot traffic after 3 to 4 days.

PROPERTIES

PALACE TERRACOTTA & STONE SEALER is a traditional linseed oil-based treatment for the protection and enhancement of old stone tiles, quarry tiles and terracotta floors. It provides a water repellent, semi-sheen protective finish which deepens and enhances the colour intensity of natural stone and can be buffed and built up to a gloss finish where required.

COVERAGE

Depending on surface texture and porosity, one litre of **PALACE TERRACOTTA & STONE SEALER** will be sufficient to protect up to 40 square metres of Terracotta surface per 1 litre pack for a single coat application depending on surface absorptive properties.

STORAGE AND PACKAGING

PALACE TERRACOTTA & STONE SEALER is supplied in 1 litre bottles packed 6 per case.

HEALTH AND SAFETY

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes damage to organs Central nervous system through prolonged or repeated exposure if inhaled. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do NOT induce vomiting. **IF SWALLOWED:** Immediately call a doctor / NHS Direct. **IF ON SKIN:** Wash with plenty of soap and water. Do not breathe vapours. **IF INHALED:** Remove victim to fresh air and keep in a position comfortable for breathing. Do not get in eyes, on skin, or on clothing. **IF ON SKIN** Remove immediately all contaminated clothing. Rinse skin with water/shower. Store in a well-ventilated place. Keep container tightly closed. Keep cool.



DANGER

QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at:

<http://www.palacechemicals.co.uk>

DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or control over where and how our products are stored and used. All products are sold and guaranteed subject to our terms and conditions of sale, copies of which may be obtained on request.



EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

PALACE CHEMICALS LTD

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 – FAX: 0151 448 1982

E-MAIL: SALES@PALACECHEMICALS.CO.UK