

Ver 04 - PALFG 28.10.24

# FENCEGUARD

## TIMBER TREATMENT FOR OUTDOOR STRUCTURES

- BRUSH APPLIED TIMBER TREATMENT
- DRIES TO A WATER REPELLENT FILM
- UV STABLE OXIDE BASED COLOURS
- PROTECTS AGAINST WATER INGRESS
- SUITABLE FOR ROUGH-SAWN TIMBERS

### TECHNICAL SUMMARY

UNIT SIZE 5 LITRES

COLOURS

6

AUTUMN GOLD  
CHESTNUT BROWN  
FOREST GREEN  
LUNAR GREY  
RED CEDAR  
MIDNIGHT BLACK



### PALACE FENCEGUARD

A water-based, low odour timber treatment providing long lasting outdoor protection for rough sawn timber. The water repellent, UV resistant finish is perfect for shielding fencing and garden sheds, or any other outdoor rough sawn garden construction from the ravages of rain and bright sunlight.

UV STABLE OXIDE  
BASED COLOURS

AVAILABLE IN  
6 COLOURS

# FENCEGUARD

## Exterior Timber Treatment



### DESCRIPTION

**PALACE FENCEGUARD** is a water-based low odour timber treatment, specially formulated to provide attractive, long lasting outdoor protection for rough sawn timber. The water repellent, UV resistant finish is perfect for shielding fencing and garden sheds, or any other outdoor rough sawn garden construction from the ravages of rain and bright sunlight. **FENCEGUARD** is available in 6 colours including: Autumn Gold, Chestnut Brown, Forest Green, Lunar Grey, Red Cedar and the new Midnight Black offering the discerning gardener a range of shades to suit all seasons and selections of garden design. **FENCEGUARD** is safe to use in and around garden plants and foliage, its water based properties make splashes easy to clean from surround areas not intended for treatment. Fenceguard is supplied in 5 litre re-usable, easy seal buckets, allowing direct application by brush straight onto timber.

### SURFACE PREPARATION

Ensure all timbers are structurally sound, dry and free from loose surface coatings or growths of moss, lichen and algae (external). For timbers heavily coated with algae growth and moulds, a pre-treatment of **ABICIDE FUNGICIDAL WASH** is recommended prior to applying **FENCEGUARD**, this will eradicate the possibility of further growth damaging the subsequently applied coating. All fabrication work ie, planing, sawing & boring should be completed prior to treatment and any timbers in direct contact with the ground, or affected by post treatment cutting should receive an application of **PALACE WOOD PRESERVATIVE** prior to treatment with **FENCEGUARD**.

### APPLICATION METHOD

Timbers recently saturated by rainfall, or when there is the likelihood of imminent rainfall (within 24 hours of application) are conditions to avoid if the coating is to have the chance to dry to its optimum appearance and protective capability. Also temperatures below 10°C are not conducive to rapid drying and should be avoided. **FENCEGUARD** is not intended for application to decking timbers, garden furniture, hardwoods or smooth-planed structures. Timber previously coated with an oil-based treatment such as **CREOSOTE**, should be well weathered before the wood will be sufficiently porous to receive the **FENCEGUARD** treatment. Children and pets should also be kept away from treated timbers until they are completely dry and free of any traces of product.

### PRECAUTIONS

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. After contact with skin wash immediately with plenty of soap and water or a recognised skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice. May be harmful if swallowed. Keep out of reach of children. Keep away from food, drink and animal feeding products.

### COVERAGE

Depending upon the texture and porosity of the timber to be treated, **FENCEGUARD** when applied as a single coat will cover at the rate of 1 litre per 4 to 6 square metres, either by brush or spray application method. In warm summer conditions, allow 2 to 6 hours drying time. When applying a second coat always make sure the first is dry, otherwise allow for a longer drying period. Clean equipment immediately with warm, soapy water and rinse thoroughly.

**NOTE:** The colour label on the container indicates approximate colour only.

### COLOURS AVAILABLE



AUTUMN GOLD



CHESTNUT BROWN



FOREST GREEN



RED CEDAR



LUNAR GREY



MIDNIGHT BLACK

### STORAGE AND PACKAGING

Fenceguard is available in 5 litre re-sealable polypropylene containers. Store in cool, well-ventilated conditions away from direct sources of heat. When transporting the container always ensure it is secured in a stable upright position and retained to prevent movement during carriage.

### HEALTH AND SAFETY

Always ensure that appropriate PPE & overalls are worn when applying this product. Wash hands after use and launder stained clothing. A complete PALACE material safety data sheet is available on request or online at [www.palacechemicals.co.uk](http://www.palacechemicals.co.uk)



EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

**PALACE CHEMICALS LTD**

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 – FAX: 0151 448 1982

E-MAIL: [SALES@PALACECHEMICALS.CO.UK](mailto:SALES@PALACECHEMICALS.CO.UK)

# FENCEGUARD

## Exterior Timber Treatment



### QUALITY AND ENVIRONMENT

All Palace Chemicals products are manufactured under a BSI accredited ISO 9001:2015 Quality Management System, along with an ISO 14001 Environmental Management system continually working to reduce our carbon footprint.

### TECHNICAL ADVISORY SERVICE

Should more specific technical information be required, contact the Palace Technical helpline on: **0151 486 6101**.

For a Technical Specification and quantity requirements, visit our 'TilingSpecifier' on the Palace website at:

**<http://www.palacechemicals.co.uk>**

### DISCLAIMER

The information provided by this Technical data sheet is given in good faith and is to the best of our current knowledge true and accurate. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or control over where and how our products are stored and used. All products are sold and guaranteed subject to our terms and conditions of sale, copies of which may be obtained on request.

TECHNICAL SUMMARY	
UNIT SIZE	5 Litres
COLOURS	6



EN ISO 45001



OHS 596309

EN ISO 14001



EMS 85788

EN ISO 9001



FM 01010

**PALACE CHEMICALS LTD**

SPEKE HALL INDUSTRIAL ESTATE

SPEKE LIVERPOOL L24 1YA

TEL: 0151 486 6101 – FAX: 0151 448 1982

E-MAIL: [SALES@PALACECHEMICALS.CO.UK](mailto:SALES@PALACECHEMICALS.CO.UK)